SkyRibbon IntelliHue Wall Washing

Date: _____
Type: _____
Firm Name: _____
Project: _____

Recessed linear interior LED wall washing luminaire with intelligent white and color light



Introducing SkyRibbon IntelliHue Wall Washing Powercore, a recessed linear interior LED wall washing luminaire offering high-quality intelligent color and white light from the same luminaire. IntelliHue is an advanced approach to color mixing that gives users the ability to precisely target a full spectrum of saturated color and high-quality white light, granting an unprecedented level of design freedom. Brilliant light output and industry-leading controls make luminaires ideal for a variety of interior wall washing applications. Users can rotate LED modules from 0° to 90° to evenly wash walls top to bottom regardless of luminaire setback. Multiple housing options accommodate a number of installation methods.

- Color-changing and high-quality white light from the same luminaire—IntelliHue is an advanced approach to color mixing that enables high-quality intelligent color and white light from a single luminaire. Multiple channels of LED light sources combine to produce a full spectrum of precisely controllable light, including millions of saturated colors, pastels, and uniform white light with CRI of greater than 85 in the 2700 K – 4000 K range.

Product page

Beam Angle	20° x 20°, 30° x 30°, 30° x 60°, 35° x 105°, 40° x 80°, 65° x 65°, 70° x 95°, 90° x 90°
Lumens @ 4000 K*	1,813 to 2,867
LED Channels[§]	Red/Green/Blue/Mint White/4000 K

Input Voltage	120 VAC/220 to 240 VAC/277 VAC, 50/60 Hz
Weight	4.7 kg (10.4 lb)
Housing Material	Steel
Approbations	UL/cUL, FCC Class A, CE
Environment	Dry/Damp Location, IP20
Applications	Wall Washing

20° x 20° Specification Sheets

PDF Download	Beam Angle	Lumens @ 4000 K*	Efficacy	Power	Weight	Item Number	12 NC
120 VAC, 20° x 20° Beam Angle	20° x 20°	1,451	33.4	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668
220 – 240 VAC, 20° x 20° Beam Angle	20° x 20°	1,451	33.4	66 W	4.7 kg (10.4 lb)	123-000072-01	910503704253
277 VAC, 20° x 20° Beam Angle	20° x 20°	1,451	33.4	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668

COLORKINETICS

30° x 30° Specification Sheets

PDF Download	Beam Angle	Lumens @ 4000 K*	Efficacy	Power	Weight	Item Number	12 NC
120 VAC, 30° x 30° Spread Lens	30° x 30°	1,245	28.6	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668
220 – 240 VAC, 30° x 30° Spread Lens	30° x 30°	1,245	28.6	66 W	4.7 kg (10.4 lb)	123-000072-01	910503704253
277 VAC, 30° x 30° Spread Lens	30° x 30°	1,245	28.6	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668

30° x 60° Specification Sheets

PDF Download	Beam Angle	Lumens @ 4000 K*	Efficacy	Power	Weight	Item Number	12 NC
120 VAC, 30° x 60° Spread Lens	30° x 60°	1,209	27.9	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668
220 – 240 VAC, 30° x 60° Spread Lens	30° x 60°	1,209	27.9	66 W	4.7 kg (10.4 lb)	123-000072-01	910503704253
277 VAC, 30° x 60° Spread Lens	30° x 60°	1,209	27.9	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668

35° x 105° Specification Sheets

PDF Download	Beam Angle	Lumens @ 4000 K*	Efficacy	Power	Weight	Item Number	12 NC
120 VAC, 35° x 105° Spread Lens	35° x 105°	1,223	28.2	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668
220 – 240 VAC, 35° x 105° Spread Lens	35° x 105°	1,223	28.2	66 W	4.7 kg (10.4 lb)	123-000072-01	910503704253
277 VAC, 35° x 105° Spread Lens	35° x 105°	1,223	28.2	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668

40° x 80° Specification Sheets

PDF Download	Beam Angle	Lumens @ 4000 K*	Efficacy	Power	Weight	Item Number	12 NC
120 VAC, 40° x 80° Spread Lens	40° x 80°	1,214	28	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668
220 – 240 VAC, 40° x 80° Spread Lens	40° x 80°	1,214	28	66 W	4.7 kg (10.4 lb)	123-000072-01	910503704253
277 VAC, 40° x 80° Spread Lens	40° x 80°	1,214	28	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668

65° x 65° Specification Sheets

PDF Download	Beam Angle	Lumens @ 4000 K*	Efficacy	Power	Weight	Item Number	12 NC
120 VAC, 65° x 65° Spread Lens	65° x 65°	1,212	27.9	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668
220 – 240 VAC, 65° x 65° Spread Lens	65° x 65°	1,212	27.9	66 W	4.7 kg (10.4 lb)	123-000072-01	910503704253
277 VAC, 65° x 65° Spread Lens	65° x 65°	1,212	27.9	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668

70° x 95° Specification Sheets

PDF Download	Beam Angle	Lumens @ 4000 K*	Efficacy	Power	Weight	Item Number	12 NC
120 VAC, 70° x 95° Spread Lens	70° x 95°	1,179	27.1	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668
220 – 240 VAC, 70° x 95° Spread Lens	70° x 95°	1,179	27.1	66 W	4.7 kg (10.4 lb)	123-000072-01	910503704253
277 VAC, 70° x 95° Spread Lens	70° x 95°	1,179	27.1	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668

90° x 90° Specification Sheets

PDF Download	Beam Angle	Lumens @ 4000 K*	Efficacy	Power	Weight	Item Number	12 NC
120 VAC, 90° x 90° Spread Lens	90° x 90°	919	21.1	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668
220 – 240 VAC, 90° x 90° Spread Lens	90° x 90°	919	21.1	66 W	4.7 kg (10.4 lb)	123-000072-01	910503704253
277 VAC, 90° x 90° Spread Lens	90° x 90°	919	21.1	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668

* Lumen output measurements comply with IES LM-79-08 testing procedures.
§ Correlated color temperature (CCT) complies with ANSI C78.377-2008 for the chromaticity of solid state lighting products.

COLORKINETICS

© 2019 Signify Holding. All rights reserved. Specifications are subject to change without notice. No representation or warranty as to the accuracy or completeness of the information included herein is given and any liability for any action in reliance thereon is disclaimed.

15 Jan 2019