



9MX056 TL-D / TL5 swivel device

Maxos accessories

The swivel device is a versatile mechanical connecting device for Maxos TL-D and TL5 light-lines and enables variable angles between the light-lines. The minimum angle is 45 degrees. Due to its attractive design it is often used in application areas such as shops, schools and museums. Up to four light-lines can be connected with one swivel device. The housing is made of plastic, with a white or silver coating, and with inner supporting elements made of steel. If needed, the swivel device can accommodate lighting control sensors, loudspeakers, etc. It is pre-mounted with an adjustable quick hanger with a 1.25 m steel suspension wire. One dedicated coupling piece (9MX056 CP-SD WH/SI) per trunking section is necessary to connect the trunking to the swivel device. Electrical components for mains feed-through have to be ordered as required.

Benefits

٠ -

Versions



9MX056 CP WH



9MX056 BC49 SI



Electrical supply connector 7-pole



9MX056 CPI

Maxos accessories

Versions



9MX056 CP SI

Product details



Maxos 4MX056 TL-D extended trunking section M300/E300/ M600/E600 and blind cover, used to close the spaces in the trunking where no electrical units are mounted

General Information	
Product family code	9MX056
Product family code	9MX056
Approval and Application	
Ingress protection code	-
Ingress protection code	-
Ingress protection code	-

General Information

Full Product Name	Accessory color
9MX056 CP WH	White
9MX056 BC49 WH	White
9MX056 BC49 SI	Silver
9MX056 BC58 WH	White
9MX056 BC58 SI	Silver
9MX056 EC7	-
	9MX056 CP WH 9MX056 BC49 WH 9MX056 BC49 SI 9MX056 BC58 WH 9MX056 BC58 SI

Order Code	Full Product Name	Accessory color
03217400	9MX056 EC7 (10PCS)	-
10809100	9MX056 CPI	-
10824400	9MX056 EP WH SET	White
10825100	9MX056 EP SI SET	Silver
10808400	9MX056 CP SI	Silver

Operating and Electrical

Maxos accessories

	Full Product	Input	Input	Line	Line
Order Code	Name	Voltage	Voltage	Frequency	Frequency
10807700	9MX056 CP	-	-	-	-
	WH				
60157899	9MX056 BC49	-	-	-	-
	WH				
60158599	9MX056 BC49	-	-	-	-
	SI				
53881299	9MX056 BC58	-	-	-	-
	WH				
53888199	9MX056 BC58	-	-	-	-
	SI				

	Full Product	Input	Input	Line	Line
Order Code	Name	Voltage	Voltage	Frequency	Frequency
13179200	9MX056 EC7	220 to 240	220 to 240	50 to 60 Hz	50 to 60 Hz
		V	V		
03217400	9MX056 EC7	220 to 240	220 to 240	50 to 60 Hz	50 to 60 Hz
	(10PCS)	V	V		
10809100	9MX056 CPI	-	-	-	-
10824400	9MX056 EP	-	-	-	-
	WH SET				
10825100	9MX056 EP SI	-	-	-	-
	SET				
10808400	9MX056 CP SI	-	-	-	-

Approval and Application

Order Code	Full Product Name	Protection class IEC	Protection class IEC
10807700	9MX056 CP WH	-	-
60157899	9MX056 BC49 WH	-	-
60158599	9MX056 BC49 SI	-	-
53881299	9MX056 BC58 WH	-	-
53888199	9MX056 BC58 SI	-	-
13179200	9MX056 EC7	Safety class I	Safety class I

Order Code	Full Product Name	Protection class IEC	Protection class IEC
03217400	9MX056 EC7 (10PCS)	Safety class I	Safety class I
10809100	9MX056 CPI	-	-
10824400	9MX056 EP WH SET	-	-
10825100	9MX056 EP SI SET	-	-
10808400	9MX056 CP SI	-	-

