



TownGuide Performer – Designed around your needs

TownGuide Performer

The TownGuide Performer family consists of six recognizable yet modern shapes: Flat Cone, Bowl, Classic Cone, Classic, T and Tzero. All are available with a clear bowl. Except for Tzero, also a frosted bowl can be chosen. With an extensive range of lumen packages and a choice of light colors and operating lifetimes, it is easy to select the version that best suits your project's specific requirements. In addition, TownGuide Performer has a variety of control system options that can make it an integral part of your smart energy-reduction programs – from stand-alone LumiStep and DynaDimmer, SDU switch-dim control, through to seamless remote connectivity with CityTouch lighting management software. Installation is easy. Thanks to the bayonet whistle connector with integrated gland located in the spigot, the luminaire does not have to be opened at all for installation. Philips has made every effort to make the Total Cost of Ownership (TCO) of the luminaire as attractive as possible. And as TownGuide Performer is a dedicated LED luminaire, compatible with a variety of control systems, the energy and maintenance cost savings compared to conventional lighting are significant.

Benefits

- Six recognizable yet modern designs that blend in with, and enhance, their surroundings
- LED light sources, in combination with a wide choice of optics, ensure that the optimal configuration can be obtained for your application. The state-of-the-art LEDs increase visual comfort for motorists, cyclists and pedestrians.
- Considerable reduction in energy usage and carbon footprint compared to HPL mercury, SON-T and PL-L compact fluorescent lamps; further energy savings achievable when using CLO or dimming options (can amount to as much as 80% compared to HPL mercury)

Features

- Dedicated LED luminaire, optimized for minimum Total Cost of Ownership
- Wide choice of lumen packages, ranging from 1,200 to 7,000 lumens (GRN) or 4,000 to 12,000 lumens (ECO)
- Choice of light colors 3000 K (warm white) and 4000 K (neutral white)
- Long lifetime of 100,000 hours (GRN) or 80,000 hours (ECO) at L80B10
- Bayonet whistle connector for easy installation without opening the luminaire
- Suitable for new installations or one-to-one replacement in existing installations
- Vandal-resistant (IK10), ingress protection (IP66)
- TailorFit PCB technology
- Standard 3-year warranty program; as a service, we offer extended warranties or lifecycle services

Application

- Residential areas: residential streets, cycle paths & footpaths, roundabouts, squares, parks & playgrounds, parking areas
- City centers: side streets, squares, parks & playgrounds, cycle paths & footpaths, parking areas, roundabouts, shopping & pedestrian areas
- Area and Transportation: industrial areas, parking areas, petrol stations, airports, harbors, public transport areas
- Sports: parking areas

Versions

OPPR BDP100i 0021

OPPR BDP100i 0001



OPPR BDP100i 0005

BDP102 TownGuide Performer
Classic cone, clear



TownGuide Performer

Versions



BDP103 TownGuide Performer
Classic T, clear



BDP104 TownGuide Performer T,
clear

Dimensional drawing

TownGuide Performer

Product details



OPDP_BDP100i_0011-Detail
photo



OPDP_BDP100i_0001-Detail
photo



OPDP_BDP100i_0003-Detail
photo



OPDP_BDP100i_0007-Detail
photo



OPDP_BDP100i_0009-Detail
photo



TownGuide_Performe-
BDP100_105-DPP.TIF

General Information	
CE mark	Yes
Driver included	Yes
Flammability mark	-
Light source replaceable	Yes
Number of gear units	Unit
Light Technical	
Standard tilt angle side entry	-
Standard tilt angle post-top	0°
Approval and Application	
Mech. impact protection code	IK10
Ingress protection code	IP66
Surge Protection (Common/Differential)	Luminaire surge protection level up to 6 kV differential mode and 6 kV common mode
Over Time Performance (IEC Compliant)	
Driver failure rate at 5,000 hours	0.5 %

General Information

Order Code	Full Product Name	Glow-wire test	Lamp family code	Product family code
34715700	BDP105 LED70/740 DS PCC GR D9 62P	Temperature 650 °C, duration 5 s	LED70	BDP105
30244600	BDP100 LED30/740 DM PCC SI CLO-DDF1 76P	Temperature 650 °C, duration 5 s	LED30	BDP100
05918400	BDP101 LED60/740 DW PCC SI 62P	-	LED60	BDP101
31985700	BDP102 LED50/830 DM PCC GR MSP 62P	Temperature 650 °C, duration 5 s	LED50	BDP102
05914600	BDP103 LED60/740 DW PCC SI 62P	-	LED60	BDP103
34713300	BDP104 LED70/740 DRW PCC GR D9 62P	Temperature 650 °C, duration 5 s	LED70	BDP104

Light Technical (1/2)

Order Code	Full Product Name	Luminaire light beam spread	Light source colour	Correlated Colour Temperature	Optical cover type
34715700	BDP105 LED70/740 DS PCC GR D9 62P	75°	740 neutral white	4000 K	Polycarbonate bowl/cover clear
30244600	BDP100 LED30/740 DM PCC SI CLO-DDF1 76P	53° x 71°	740 neutral white	4000 K	Polycarbonate bowl/cover clear
05918400	BDP101 LED60/740 DW PCC SI 62P	50° x 70°	740 neutral white	4000 K	Polycarbonate bowl/cover frosted
31985700	BDP102 LED50/830 DM PCC GR MSP 62P	53° x 71°	830 warm white	3000 K	Polycarbonate bowl/cover clear

Order Code	Full Product Name	Luminaire light beam spread	Light source colour	Correlated Colour Temperature	Optical cover type
05914600	BDP103 LED60/740 DW PCC SI 62P	50° x 70°	740 neutral white	4000 K	Polycarbonate bowl/cover frosted
34713300	BDP104 LED70/740 DRW PCC GR D9 62P	39° x 96°	740 neutral white	4000 K	Polycarbonate bowl/cover clear

Light Technical (2/2)

Order Code	Full Product Name	Colour rendering index (CRI)	Luminous Flux	Number of light sources	Optic type outdoor	Upwards light output ratio
34715700	BDP105 LED70/740 DS	70	4,830 lm	8	Distribution symmetrical	0

Order Code	Full Product Name	Colour rendering index (CRI)	Luminous Flux	Number of light sources	Optic type outdoor	Upwards light output ratio
	PCC GR D9 62P					

TownGuide Performer

Order Code	Full Product Name	Colour rendering index (CRI)	Luminous Flux	Number of light sources	Optic type outdoor	Upwards light output ratio
30244600	BDP100 LED30/740 DM PCC SI CLO-DDF1 76P	70	2,204 lm	4	Distribution medium	3
05918400	BDP101 LED60/740 DW PCC SI 62P	70	4,740 lm	-	Distribution wide	3
31985700	BDP102 LED50/830	80	3,900 lm	6	Distribution medium	3

Order Code	Full Product Name	Colour rendering index (CRI)	Luminous Flux	Number of light sources	Optic type outdoor	Upwards light output ratio
05914600	BDP103 LED60/740 DW PCC SI 62P	70	4,500 lm	-	Distribution wide	3
34713300	BDP104 LED70/740 DRW PCC GR D9 62P	70	4,620 lm	8	Distribution residential wide	3

Operating and Electrical

Order Code	Full Product Name	Power Consumption
34715700	BDP105 LED70/740 DS PCC GR D9 62P	45.5 W
30244600	BDP100 LED30/740 DM PCC SI CLO-DDF1 76P	19.6 W
05918400	BDP101 LED60/740 DW PCC SI 62P	39 W

Order Code	Full Product Name	Power Consumption
31985700	BDP102 LED50/830 DM PCC GR MSP 62P	41 W
05914600	BDP103 LED60/740 DW PCC SI 62P	39 W
34713300	BDP104 LED70/740 DRW PCC GR D9 62P	45.5 W

Controls and Dimming

Order Code	Full Product Name	Dimmable
34715700	BDP105 LED70/740 DS PCC GR D9 62P	Yes
30244600	BDP100 LED30/740 DM PCC SI CLO-DDF1 76P	Yes
05918400	BDP101 LED60/740 DW PCC SI 62P	No

Order Code	Full Product Name	Dimmable
31985700	BDP102 LED50/830 DM PCC GR MSP 62P	No
05914600	BDP103 LED60/740 DW PCC SI 62P	No
34713300	BDP104 LED70/740 DRW PCC GR D9 62P	Yes

Mechanical and Housing

Order Code	Full Product Name	Housing Colour
34715700	BDP105 LED70/740 DS PCC GR D9 62P	Grey
30244600	BDP100 LED30/740 DM PCC SI CLO-DDF1 76P	Silver
05918400	BDP101 LED60/740 DW PCC SI 62P	Silver

Order Code	Full Product Name	Housing Colour
31985700	BDP102 LED50/830 DM PCC GR MSP 62P	Grey
05914600	BDP103 LED60/740 DW PCC SI 62P	Silver
34713300	BDP104 LED70/740 DRW PCC GR D9 62P	Grey

Application Conditions

Order Code	Full Product Name	Maximum dim level
34715700	BDP105 LED70/740 DS PCC GR D9 62P	0% (digital)
30244600	BDP100 LED30/740 DM PCC SI CLO-DDF1 76P	50%
05918400	BDP101 LED60/740 DW PCC SI 62P	Not applicable

Order Code	Full Product Name	Maximum dim level
31985700	BDP102 LED50/830 DM PCC GR MSP 62P	Not applicable
05914600	BDP103 LED60/740 DW PCC SI 62P	Not applicable
34713300	BDP104 LED70/740 DRW PCC GR D9 62P	0% (digital)

Polar Wide Diagrams

Polar Normal (separate) - BDP100I -
910500991164

Polar Normal (separate) - BDP100I -
910500991211

Polar Normal (separate) - BDP100I -
910925863304

Polar Normal (separate) - BDP100I -
910925863302

Polar Normal (separate) - BDP100I -
910925866481

Polar Normal (separate) - BDP100I -
910925866485

