



Annecy CDS 560

Metronomis Annecy

The Annecy is ideally suited to modern residential areas. Variations in lighting effect and design can be achieved through the use of a clear, opaque or painted cover. By using different light sources and optical elements, it is possible to create different accents and atmospheres within the living environment.

Benefits

- Total solution with both luminaires and supports forming part of a complete, integrated concept
- Huge range of optical elements and light sources makes it possible to create different atmospheres within the city using a single, perfectly coordinated system
- Dedicated masts and brackets match the style of the luminaires - five mast designs in steel, aluminum and wood with heights from 3.5 to 12 m

Features

- Wide range of optical elements and light sources
- Dedicated masts and brackets – five mast designs in steel, aluminum and wood, with heights from 3.5 to 12 m

Application

- Urban and architectural areas
- Commercial and business centers

Specifications

Type	CDS560	Light source	HID:
			- 1 x MASTER CosmoWhite CPO-TT / PGZ12 / 45, 60, 90, 140 W
			- 1 x MASTER CityWhite CDO-TT / E27 / 50, 70 W
			- 1 x MASTER CityWhite CDO-TT / E40 / 100, 150 W
			- 1 x MASTER Colour CDM-T / G12 / 35, 70, 150 W
			- 1 x MASTER SDW-T / PG12-1 / 50, 100 W

	- 1 x SON / E27 / 50, 70 W
	- 1 x SON / E40 / 100, 150 W
	- 1 x SON-T / E27 / 50, 70 W
	- 1 x SON-T / E40 / 100, 150 W
	- 1 x SON-T APIA Xtra / 50, 70, 100 W
	Compact fluorescent:
	- 1 x MASTER PL-T 4 Pin / GX24q-3 or 4* / 32, 42 W
	- *depends on wattage
	Induction lamp system:
	- MASTER QL system / 55 W
Lamp included	Yes (K or lamp color 628, 728, 830, 840)
	No
Gear	Electro magnetic (low loss), 240 V / 50 Hz
	Electronic, 220 - 240 V / 50 - 60 Hz:
	- Electronic (EB)
Optic (elements)	Louver (LO)
	Refractor, prismatic (PR)
	Diffuser (DF)
	Rotationally symmetrical reflector (S)
	Road lighting reflector, asymmetrical (A)
	Indirect (IO)**
Optical cover	Transparent bowl and cover (TT)
	Transparent bowl and opal cover (TO)
	Transparent bowl and painted cover (TP)
	Opal bowl and cover (OO)
	Opal bowl and painted cover (OP)

Ignitor	Semi-parallel (SP)
	Semi-parallel, self-stopping (ST)
	Semi-parallel digital (SND)
Options	Photocell: Minicell (P3)
	Filter coil (F)
Materials and finishing	Housing: high-pressure, die-cast aluminum
	Bowls and bowl covers: polycarbonate
	Refractor and diffuser: polymethylmethacrylic-imide
	Louvers: high-pressure, die-cast aluminum
	Reflector assemblies: aluminum
	Adapters: die-cast aluminum
Color	Dark grey (GR)
	Akzo or RAL colors available on request
Installation	Post top mounting: axial entry Ø 60 / 76 mm
	Side entry mounting: lateral entry Ø 42 - 60 mm with side entry adapter
	Recommended mounting height: 4 - 6 m
Accessories	Adapter for side entry, Ø 42 - 60 mm
Remarks	Compatible with various Metronomis brackets
	**Dedicated indirect optic (IO) preventing light nuisance (E2 classification according to CIE 126-1997)
Main applications	Urban and architectural areas, commercial and business centers

Versions

