



Metronomis – bespoke solutions

Metronomis Bordeaux

Metronomis is a family of ten highly distinctive luminaires and dedicated supports (masts and brackets), which can be used with a wide variety of optics to provide architects and lighting designers with the total solution needed to create a unified, consistent lighting design that still reflects the differences in urban culture and history. In its daytime appearance, Metronomis integrates harmoniously with any street scene, while its night-time appearance is both functional – guiding people and traffic safely through the city – and decorative, creating a pleasant ambience in city squares and pedestrian precincts. As the current range is based on conventional light sources, four highly innovative, LED-dedicated designs have been developed, echoing the original silhouette but retaining flexibility and modularity as key characteristics. The Metronomis LED range offers a number of new ways to personalize your urban projects. Please check out the Metronomis LED luminaire variants.

Benefits

- Total solution with both luminaires and supports forming part of a complete, integrated concept
- Huge range of optical elements and light sources makes it possible to create different atmospheres within the city using a single, perfectly coordinated system
- Dedicated masts and brackets match the style of the luminaires

Features

- Wide range of optical elements and light sources
- Five mast designs in steel, aluminum and wood, with heights from 3.5 to 12 m

Application

- Urban and architectural areas
- Commercial and business centers

Specifications

Type	CDS592/594
Light source	<p>HID:</p> <ul style="list-style-type: none"> - 1 x MASTER CosmoWhite CPO-TW / PGZ12 / 45, 60, 90, 140 W - 1 x MASTER CityWhite CDO-TT / E27 / 50, 70 W - 1 x MASTER CityWhite CDO-TT / E40 / 100, 150 W - 1 x MASTER Colour CDM-T / G12 / 35, 70, 150 W - 1 x MASTER SDW-T / PG12-1 / 50, 100 W - 1 x SON / E27 / 50, 70 W - 1 x SON / E40 / 100, 150 W - 1 x SON-I / E27 / 50, 70 W - 1 x SON-T / E27 / 50, 70 W - 1 x SON-T / E40 / 100, 150 W - 1 x SON-T APIA Xtra / 50, 70, 100 W <p>Compact fluorescent:</p> <ul style="list-style-type: none"> - 1 x MASTER PL-T 4 Pin / GX24q-3 or 4* / 32, 42 W - *depends on wattage <p>Induction lamp system:</p> <ul style="list-style-type: none"> - MASTER QL system / 55 W
Lamp included	<p>Yes (K or lamp color 628, 728, 830, 840)</p> <p>No</p>
Gear	<p>Electronic, 220 - 240 V / 50 - 60 Hz:</p> <ul style="list-style-type: none"> - Electronic (EB)
Optic (elements)	<p>Louver (LO)</p> <p>Refractor, prismatic (PR)</p> <p>Diffuser (DF)</p> <p>Rotation-symmetrical reflector (S)</p> <p>Road-lighting reflector, asymmetrical (A)</p>

Optical cover	<p>Transparent bowl and cover (TT)</p> <p>Opal bowl and transparent cover (OT)</p> <p>Transparent bowl and opal cover (TO)</p> <p>Opal bowl and cover (OO)</p>
Ignitor	<p>Semi-parallel (SP)</p> <p>Semi-parallel, self-stopping (ST)</p> <p>Semi-parallel digital (SND)</p>
Options	<p>Photocell: Minicell (P3)</p> <p>Filter coil (F)</p>
Materials and finishing	<p>Housing: high-pressure, die-cast aluminum</p> <p>Decorative arms: die-cast aluminum</p> <p>Bowls and bowl covers: polycarbonate</p> <p>Refractor and diffuser: polymethylmethacrylic-imide</p> <p>Louvers: high-pressure, die-cast aluminum</p> <p>Reflector assemblies: aluminum</p> <p>Adapters: die-cast aluminum</p>
Color	<p>Dark grey (GR)</p> <p>Akzo or RAL colors available on request</p>
Installation	<p>Side-entry mounting: lateral entry Ø 42 - 60 mm with side-entry adapter</p> <p>Catenary mounting with catenary adapter</p> <p>Recommended mounting height: 4 - 6 m</p>
Accessories	<p>Adapter for side entry, Ø 42 - 60 mm, ZRP551</p> <p>Catenary adapter, ZRP552</p>
Remarks	Compatible with various Metronomis brackets
Main applications	Urban and architectural areas, commercial and business centers

Dimensional drawing

Metronomis CDS500

Metronomis CDS500

Approval and Application

Mech. impact protection code	IK09
------------------------------	------

General Information

CE mark	CE mark
Color	Gray
Optical cover/lens type	TT
Design Award Winner mark	Design Award Winner
ENEC mark	ENEC mark
Gear	CONV
Glow-wire test	850/5
Lamp power	70
Number of light sources	1
Optic type	Symmetrical
Optical element	No

General Information

order code	Lamp family code	Product Family Code
22568500	CDM-T	CDS594
84602600	CDO-TT	CDS592
67661600	CDO-TT	CDS592

