



Metronomis – turning vision into reality

Metronomis Bordeaux

Metronomis is a family of ten highly distinctive luminaires and dedicated supports (columns and brackets) which can be used with a wide variety of optics to provide architects and lighting designers with the total solution needed to create a unified, consistent lighting design that still reflects the differences in urban culture and history. In its daytime appearance, Metronomis integrates harmoniously with any street scene, while its night-time appearance is both functional – guiding people and traffic safely through the city – and decorative, creating a pleasant ambience in city squares and pedestrian precincts.

Benefits

- Total solution with both luminaires and supports forming part of a complete, integrated concept
- Huge range of optical elements and light sources makes it possible to create different atmospheres within the city using a single, perfectly coordinated system

Features

- Wide range of optical elements and light sources
- Dedicated masts and brackets – five mast designs in steel, aluminium and wood, with heights from 3.5 to 12 m

Application

- Urban and architectural areas
- Commercial and business centres

Specifications

Type	CDS592/594	Light source	HID:
			- 1 x MASTER CosmoWhite CPO-TW / PGZ12 / 45, 60, 90, 140 W
			- 1 x MASTER CityWhite CDO-TT / E27 / 70 W

Metronomis Bordeaux

	- 1 x MASTER CityWhite CDO-TT / E40 / 100, 150 W
	- 1 x MASTER Colour CDM-T / G12 / 35, 70, 150 W
	- 1 x MASTER SDW-T / PG12-1 / 50, 100 W
	- 1 x SON / E27 / 50, 70 W
	- 1 x SON / E40 / 100, 150 W
	- 1 x SON-I / E27 / 50, 70 W
	- 1 x SON-T / E27 / 50, 70 W
	- 1 x SON-T / E40 / 100, 150 W
	Compact fluorescent:
	- 1 x MASTER PL-T 4 Pin / GX24q-3 or 4* / 32, 42 W
	- *depends on wattage
	Induction lamp system:
	- MASTER QL system / 55 W
Lamp included	Yes (K or lamp color 628, 728, 830, 840)
	No
Gear	Electronic, 220 - 240 V / 50 - 60 Hz:
	- Electronic (EB)
Optic (elements)	Louver (LO)
	Refractor, prismatic (PR)
	Diffuser (DF)
	Rotation-symmetrical reflector (S)
	Road-lighting reflector, asymmetrical (A)
Optical cover	Transparent bowl and cover (TT)
	Opal bowl and transparent cover (OT)
	Transparent bowl and opal cover (TO)
	Opal bowl and cover (OO)

Ignitor	Semi-parallel (SP)
	Semi-parallel, self-stopping (ST)
Options	Photocell: Minicell (P3)
	Filter coil (F)
Materials and finishing	Housing: high-pressure, die-cast aluminum
	Decorative arms: die-cast aluminum
	Bowls and bowl covers: polycarbonate
	Refractor and diffuser: polymethylmethacrylic-imide
	Louvers: high-pressure, die-cast aluminum
	Reflector assemblies: aluminum
	Adapters: die-cast aluminum
Color	Dark grey (GR)
	Akzo or RAL colors available on request
Installation	Side-entry mounting: lateral entry Ø 42 - 60 mm with side-entry adapter
	Catenary mounting with catenary adapter
	Recommended mounting height: 4 - 6 m
Accessories	Adapter for side entry, Ø 42 - 60 mm, ZRP551
	Catenary adapter, ZRP552
Remarks	Compatible with various Metronomis brackets
Main applications	Urban and architectural areas, commercial and business centers

Versions

