



FWC110/120/121 and FCC110/120 – for low-level lighting

FWC 110/120/121

FWC110/120/121 (wall-mounted) and FCC110/120 (ceiling-mounted) are attractive, low-energy luminaires for all-night security and amenity lighting. The high-reflectance white plate and translucent bowl with prismatic control produce excellent light distribution for low-level lighting of walls, corridors and surroundings.

Benefits

- Low-energy luminaires for economical all-night security and amenity lighting
- Excellent light control for low-level lighting of walls, corridors and surroundings, thanks to high optical performance of mirror and refractor bowl
- Choice of long-life lamps for low maintenance costs

Features

- Choice of long-life lamps
- Low energy consumption
- Mirror and refractor bowl

Application

- Residential areas
- Industry
- Security lighting

Specifications

Type	FWC110
	FWC/XWC120
	FWC/XWC121

Light source	FWC110
	Compact fluorescent:
	- 1 x MASTER PL-S 2 Pin / G23 / 9 W

FWC 110/120/121

	FWC/XWC120
	HID:
	- 1 x MASTER SOX-E / BY22d / 18 W
	Compact fluorescent:
	- 1 x MASTER PL-C 2 Pin / G24d-2 / 18 W
	FWC/XWC121
	HID:
	- 1 x MASTER SOX-E / BY22d / 18 W
	Compact fluorescent:
	- 1 x MASTER PL-C 2 Pin / G24d-2 / 18 W
Lamp included	Yes (K or light color 827)
Mains voltage	230 or 240 V

Option	Photocell integrated (PH)
Materials	Housing: injection-moulded ASA, non-corrosive
	Bowl: polycarbonate, translucent
	Unit plate: polycarbonate
Color	Housing: white or black (BK)
	Unit plate: white
Installation	Wall mounting
	Cable entries on all sides allow through-wiring
Remarks	Luminaires are ready-to-install versions; lamp and installation material included
Main applications	Residential areas, industry, security

