



Put people and merchandise in the best light

Long Life IR PAR30S

Optically advanced Halogen PAR lamps are designed with innovative technologies that provide superior light performance while reducing operating costs.

Benefits

- Delivers consistent quality lamp-to-lamp and throughout lifetime.
- Increased uniform beam intensity without hot spots.
- Superior beam control for effective accent lighting.

Features

- Philips reflector technology provide optimal beam control and uniform beam intensity without hot spots.
- Features IRC coating technology.
- 6000 Hour Rated Average Life †
- Available in 45 Watts Spot, Flood, Wide Flood.
- †This excludes the 130V 50W PAR30 Short which has 3000 hours. Rated average life is the length of operation (in hours) at which point an average of 50% of the lamps will still be operational and 50% will not

Application

- Ideal for retail, residential, and commercial applications. For indoor and outdoor use.

Long Life IR PAR30S

Versions




E26, PAR30/PAR30S, Wide Flood, Med



E26, PAR30/PAR30S

Dimensional drawing



Product	D	C (max)
Long Life IR 50PAR30L/IRC+/WFL40 120V 15/1	3.75 in	4.5 in
Long Life IR 50PAR30L/IRC+/SP10 120V 15/1	3.75 in	4.5 in

Long Life IR PAR30S

Approval and Application

Estimated Energy Cost Per Year	6.02 \$
--------------------------------	---------

Operating and Electrical

Voltage (Nom)	120 V
Power (Rated) (Nom)	50 W

General Information

Cap-Base	E26
Life With 3 Hour Per Day Use	3.8 a
Main Application	Accent & Downlighting
Operating Position	Universal
Rated Lifetime (Hours)	4200 h

Light Technical

Correlated Color Temperature (Nom)	2750 K
Color Rendering Index (Nom)	100
Luminous Flux (Nom)	900 lm

Mechanical and Housing

Bulb Finish	CL
Bulb Material	Hard Glass
Bulb Shape	PAR30L
Reflector Finish	Aluminized

Light Technical

Order Code	Full Product Name	Beam Angle	Beam Description	Luminous Intensity
		(Nom)		(Nom)
238006	Long Life IR 50PAR30L/IRC+/WFL40 120V 15/1	40 °	Wide Flood	1550 cd
237990	Long Life IR 50PAR30L/IRC+/SP10 120V 15/1	10 °	Spot	12000 cd

