



Brighten your home with infinite possibilities

DuraMax Reflector Flood

Philips DuraMax® Long Life Reflector Flood Bulbs reduce the hassle of replacing light bulbs every few months, since all DuraMax products last longer than standard incandescent light bulbs. Available in a variety of sizes and wattages. Use flood lights for general or ambient lighting; use spot lights to highlight artwork or architecture. Both are ideal for use in recessed cans or track lighting fixtures.

Benefits

- Philips DuraMax long life reflector bulbs last longer than standard incandescent, significantly reducing the hassle of replacing light bulbs that burn out too quickly.
- Philips DuraMax reflector floods provide a wide beam of light for general ambient lighting; DuraMax reflector spots provide a narrow beam of light for accenting.

Features

- Lasts at Least One and a Half Years!
- Medium base.
- Available in a variety of wattages.
- Available in flood version for general or ambient lighting; Available in spot version to highlight artwork or architecture.
- Available in R20: 30, 50 and 75 watt; Br30 Flood: 45, 65, and 85 watt; BR30 Spot: 65 and 85 watt; BR40 Flood: 65, 85 and 120 watt; BR40 Spot: 120 watt.
- * Based on an average of hours usage per day/7 days per week. Hours differ between products, and there are exceptions. See individual products for details.

Application

- The DuraMax flood reflectors are ideal for general or ambient lighting in recessed cans or track lighting fixtures. The DuraMax Spot reflector highlights artwork and architecture.

DuraMax Reflector Flood

Versions





LPPR I-R E17 R14 FR



LPPR I-BR BR40 FL CL

Dimensional drawing



Product

65BR/FL60/LL 120V 4/2 TP

Product	D	C (max)
45R20/LL 120V 6/1 TP	2.5 inch	3.94 inch

General Information	
Cap-Base	E26
Rated Lifetime (Hours)	2,500 hour(s)
Operating and Electrical	
Voltage (Nom)	120 V
Mechanical and Housing	
Bulb Finish	Frosted

General Information

DuraMax Reflector Flood

Order Code	Full Product Name	Operating Position
925154636310	45R20/LL 120V 6/1 TP	UNIVERSAL

Order Code	Full Product Name	Operating Position
920670136320	65BR/FL60/LL 120V 4/2 TP	H90

Light Technical

Order Code	Full Product Name	Beam Angle (Nom)	Luminous Flux
925154636310	45R20/LL 120V 6/1 TP	-	385 lm

Order Code	Full Product Name	Beam Angle (Nom)	Luminous Flux
920670136320	65BR/FL60/LL 120V 4/2 TP	60 degree(s)	625 lm

Operating and Electrical

Order Code	Full Product Name	Power Consumption
925154636310	45R20/LL 120V 6/1 TP	45 W

Order Code	Full Product Name	Power Consumption
920670136320	65BR/FL60/LL 120V 4/2 TP	65 W

Mechanical and Housing

Order Code	Full Product Name	Bulb Shape
925154636310	45R20/LL 120V 6/1 TP	R20

Order Code	Full Product Name	Bulb Shape
920670136320	65BR/FL60/LL 120V 4/2 TP	BR40

