



Product Description

Reflector diam 50 mm

Reflector lamps based on advanced spotlighting technology

Benefits

- Centre-beam intensities up to 100% higher than with conventional reflector lamps


Features

- Optic gives double reflection of part of the light emitted by the filament
- Beam spread and luminous intensity make these lamps especially suitable wherever space is limited and in small luminaires
- Direct replacement for conventional reflector lamps of all kinds
- Easy fitting and removal thanks to tapered profile

Application

- All the benefits of high-performance, high-efficiency spotlighting, simply by replacing conventional reflector lamps with ring mirror lamps of the same size and wattage
- Display lighting in shops, hotels, restaurants and homes

Dimensional drawing




Product	D
Refl 40W E14 230V NR50 30D 1CT/30	50 mm
Refl 40W E14 230V NR50 30D 1CT/30	50 mm
Refl 40W E14 240V NR50 30D FR 2BC/10	50 mm
Refl 60W E14 230V NR50 30D 1CT/30	50 mm
Refl 60W E14 230V NR50 30D 1CT/30	50 mm

Reflector diam 50 mm


General Information	
Cap-Base	E14
Rated Lifetime (Hours)	1,000 hour(s)
Nominal lifetime	1,000 hour(s)
Operating Position	UNIVERSAL
Light Technical	
Beam Angle (Nom)	30 degree(s)
Color rendering index (CRI)	100
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Frosted
Bulb Shape	NR50

Operating and Electrical

Order Code	Full Product Name	Voltage (Nom)	Power Consumption
923338544203	Refl 40W E14 230V NR50 30D 1CT/30	230 V	40 W
923338545554	Refl 40W E14 240V NR50 30D FR 2BC/10	240 V	40 W
923348744206	Refl 60W E14 230V NR50 30D 1CT/30	230 V	60 W
923348744215	Refl 60W E14 230V NR50 30D 1CT/30	230 V	60 W
926000002702	Refl 40W E14 230V NR50 30D 1CT/30	230 V	40 W




Accent Diagrams



Accent Diagram - Refl 40W E14 230V NR50 30D 1CT/30

Reflector diam 50 mm

Beam Diagrams



Beam diagram - Refl 40W E14 230V NR50 30D
1CT/30

