



The world's most efficient fluorescent lighting

MASTER TL5 High Efficiency Eco

This extremely efficient TL5 lamp (tube diameter 16 mm) saves considerable energy by simple lamp-for-lamp replacement. The TL5 HE Eco lamp offers excellent lumen maintenance and color rendering. Application areas vary from offices and industry to schools and retail environments.

Benefits

- Up to 10 % energy saving with simply changing the lamp
- The same quality of light as compared with MASTER TL5 HE lamps
- All benefits of regular TL5 lamps

Features

- High lamp efficacies up to 114 lm/W
- Up to 10% power reduction in comparison with standard MASTER TL5 HE lamps
- Fluorescent Super 80 light quality

Application

- Ideally suited for recessed, surface-mounted and suspended luminaires e.g. in offices, shops, schools, public buildings and industry (low ceiling), wherever high-quality, energy-efficient lighting is required

Warnings and Safety


- A reduction in energy consumption is only achieved with current-controlled gear.
- The lamps operate perfectly with power-controlled gear, but in that case the light output can be up to 10% higher.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

MASTER TL5 High Efficiency Eco

Versions



Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HE Eco 13=14W/840 UNP/40	17 mm	549.0 mm	556.1 mm	553.7 mm	563.2 mm
MASTER TL5 HE Eco 25=28W/830 UNP/40	17 mm	1149.0 mm	1156.1 mm	1153.7 mm	1163.2 mm

MASTER TL5 High Efficiency Eco

Approval and Application	
Energy Efficiency Label (EEL)	A+
Mercury (Hg) Content (Nom)	1.4 mg
Controls and Dimming	
Dimmable	Yes
Operating and Electrical	
Lamp Current (Nom)	0.170 A
General Information	
Cap-Base	G5
Life To 50% Failures Preheat (Nom)	25000 h
LSF Preheat 16000 h Rated	99 %
LSF Preheat 20000 h Rated	94 %
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	99 %
LSF Preheat 6000 h Rated	99 %
LSF Preheat 8000 h Rated	99 %
Light Technical	
Colour Rendering Index (Max)	85
Colour Rendering Index (Min)	80
Colour Rendering Index (Nom)	82
LLMF 12000 h Rated	92 %
LLMF 16000 h Rated	91 %
LLMF 2000 h Rated	96 %
LLMF 20000 h Rated	90 %
LLMF 4000 h Rated	95 %
LLMF 6000 h Rated	94 %
LLMF 8000 h Rated	93 %
Mechanical and Housing	
Bulb Shape	T5
Temperature	
Design Temperature (Nom)	35 °C

Approval and Application

Order Code	Full Product Name	Energy Consumption kWh/1000 h
88083000	MASTER TL5 HE Eco 13=14W/840 UNP/40	14 kWh
82588600	MASTER TL5 HE Eco 25=28W/830 UNP/40	28 kWh

Operating and Electrical

Order Code	Full Product Name	Power (Rated) (Nom)
88083000	MASTER TL5 HE Eco 13=14W/840 UNP/40	13 W

Order Code	Full Product Name	Power (Rated) (Nom)
82588600	MASTER TL5 HE Eco 25=28W/830 UNP/40	25.2 W

Light Technical (1/2)

				Correlated Colour Temperature (Nom)	Luminous Efficacy (@ Max Lumen, Rated) (Nom)
Order Code	Full Product Name	Colour Code	Colour Designation		
88083000	MASTER TL5 HE Eco	841	Cool White (CW)	4000 K	108 lm/W

				Correlated Colour Temperature (Nom)	Luminous Efficacy (@ Max Lumen, Rated) (Nom)
Order Code	Full Product Name	Colour Code	Colour Designation		
	13=14W/840 UNP/40				

MASTER TL5 High Efficiency Eco

Order Code	Full Product Name	Colour Code	Colour Designation	Correlated Colour Temperature	Luminous Efficacy (@ Max Lumen, Rated) (Nom)
				(Nom)	(Nom)
82588600	MASTER TL5 HE Eco	830	Warm White (WW)	3000 K	114 lm/W

Order Code	Full Product Name	Colour Code	Colour Designation	Correlated Colour Temperature	Luminous Efficacy (@ Max Lumen, Rated) (Nom)
				(Nom)	(Nom)
	25=28W/830 UNP/40				

Light Technical (2/2)

Order Code	Full Product Name	Luminous Efficacy (rated) (Nom)	Luminous Flux (Nom)	Luminous Flux (Rated) (Nom)
		(Nom)	(Nom)	(Rated) (Nom)
88083000	MASTER TL5 HE Eco 13=14W/840 UNP/40	92 lm/W	1350 lm	1150 lm

Order Code	Full Product Name	Luminous Efficacy (rated) (Nom)	Luminous Flux (Nom)	Luminous Flux (Rated) (Nom)
		(Nom)	(Nom)	(Rated) (Nom)
82588600	MASTER TL5 HE Eco 25=28W/830 UNP/40	103 lm/W	2900 lm	2600 lm

