



Product Description

TL Mini Standard Colours

Low-pressure mercury discharge lamps with a tubular 16 mm envelope

Benefits

- Creates atmospheres from warm white to cool daylight

Features

- 16 mm diameter tubes with moderate colour rendering

Application

- Ideal for applications where space is limited and colour rendering is not important
- Orientation lighting
- Emergency lighting

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


Versions



LPPR TL-MINI

TL Mini Standard Colours

Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL Mini 8W/33-640 FAM/10X25BOX	16 mm	288.3 mm	295.4 mm	293.0 mm	302.5 mm
TL Mini 8W/54-765 FAM/10X25BOX	16 mm	288.3 mm	295.4 mm	293.0 mm	302.5 mm

General Information	
Cap-Base	G5
Operating and Electrical	
Lamp Current (Nom)	0.145 A
Voltage (Nom)	56 V
Power Consumption	7.1 W
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Shape	T5
Approval and Application	
Energy Consumption kWh/1000 h	8 kWh
Mercury (Hg) Content (Max)	2.5 mg
Mercury (Hg) Content (Nom)	4.4 mg

Light Technical (1/2)

Order Code	Full Product Name	Chromaticity	Chromaticity	Correlated Color	
		Coordinate X (Nom)	Coordinate Y (Nom)	Color Designation	Temperature (Nom)
928001003318	TL Mini 8W/33-640 FAM/10X25BOX	0.38	0.38	Cool White (CW)	4000 K
928001005440	TL Mini 8W/54-765 FAM/10X25BOX	0.313	0.337	Cool Daylight	6500 K

Light Technical (2/2)

Order Code	Full Product Name	Color	Luminous	Luminous
		rendering index (CRI)	Efficacy (rated) (Nom)	
928001003318	TL Mini 8W/33-640 FAM/10X25BOX	59	51 lm/W	380 lm



TL Mini Standard Colours

Order Code	Full Product Name	Color	Luminous	Luminous
		rendering index (CRI)	Efficacy (rated) (Nom)	
928001005440	TL Mini 8W/54-765 FAM/10X25BOX	72	48 lm/W	335 lm

