PHILIPS

Lighting



SmartForm – top-class lighting in a fresh, appealing design

SmartForm TPS460/462/464

We all feel and perform better in a pleasant, comfortable working environment. Designed for use in offices, shops and schools, the SmartForm family of suspended mounted luminaires combines best-in-class lighting with a clean, distinctive design.These ultra-flat luminaires are available with a choice of MASTER TL5, TL5 ECO or LED light sources in rectangular and square versions with direct/indirect lighting combinations. They can also be used to form light-lines and structures.With its wide choice of very efficient and comfortable micro-optics and covers, SmartForm suspended provides the ideal solution for every situation. Lighting controls can be added for further energy saving.

Benefits

- Top-class lighting performance meets all project requirements
- Fresh-looking design
- Energy-efficient

Features

- Very slim housing – only 47 mm deep
- State-of-the-art lamps
- High-efficiency optics and covers
- Direct/indirect light distribution
- Possibility to add lighting controls

Application

- Offices
- Shops
- Schools

Specifications

Type	TPS460 (light beam, light effect cover, direct lighting)
	TPS462 (light beam, light effect cover, direct 70%/indirect 30%)
	TPS464 (light beam, light effect cover, direct 30%/indirect 70%)
Light source	Fluorescent:
	- 3 x or 4 x MASTER TL5 ECO / G5 / 13, 20 W (square version)
	- 3 x or 4 x MASTER TL5 / G5 / 14, 24 W (square version)
	- 1 x or 2 x MASTER TL5 ECO / G5 / 25, 32, 45, 50, 73 W (rectangular version)
	- 1 x or 2 x MASTER TL5 / G5 / 28, 35, 49, 54, 80 W (rectangular version)
Lamp included	Yes, TL5 ECO (lamp color 830 or 840)
	Yes, TL5 (lamp color 827 / 865, 830 or 840)
	No
Ballast	Electronic, 220 - 240 V / 50 - 60 Hz:
	- High Frequency Performer (HFP)
	- High Frequency Performer, intelligent, multi-watt (HFP-I)
	- High Frequency Regulator, 1-10 V (HFR)
	- High Frequency Regulator, DALI (HFD)
	- High Frequency Regulator DALI, touch & dimming (HFD-T)

Housing configuration (for line arrangements)	Line end, 1 phase (LE1), for ending a line
	Line feature, 1 phase (LF1), for insertion in a line
Optic	1, 2, 3, 4-lamp version:
	- Micro OLC performer high-gloss optic (C8)
	- Micro OLC performer semi-high-gloss optic (D8)
	- Micro OLC very high efficiency high-gloss optic (C8-VH)
	- Micro OLC very high efficiency semi-high-gloss optic (D8-VH)
	- Micro OLC excellent comfort high-gloss optic (C8-C)
	- Micro OLC excellent comfort semi-high-gloss optic (D8-C)
	- Micro matt mirror, ribbed cross louvers (M2)
	- Micro high-efficiency mirror, ribbed cross louvers (M2-H)
	1, 2-lamp version:
	- Micro OLC performer semi-high-gloss bi-directional optic with top reflector (T D8-BD)
	- Micro high-efficiency asymmetrical optic (A)

Specifications

Optical cover	1, 2-lamp version:
	- OLC micro-lens optic in polycarbonate cover (MLO-PC)
	- Opal cover made of polycarbonate (PCO)
	3, 4-lamp version:
	- OLC micro-lens optic made of acrylic with very-high-reflectance top reflector (T-VH AC-MLO)
	- OLC micro-lens optic made of polycarbonate with very-high-reflectance top reflector (T-VH PC-MLO)
	- Opal satinized cover made of polycarbonate with very-high-reflectance top reflector (T-VH PCO-SAT)
Connection	Push-in connection with pull relief (PIP)
	Cable, length 200 cm, with plug CEE7 (CCE)
Options	Emergency lighting: 1 hour (EL1), 3 hours (EL3)
	Lighting controls:
	- Luxsense daylight controller micro (LXM)
	- ActiLume multi controller (ACL)
	Internal PVC free wiring (PVCFR)
	Euro fuse (FU) included
Materials and color	Housing of powder coated steel, end-caps of PC-ABS
	White RAL 9016 based is standard; optional white RAL 9010 or silver grey RAL 9006 based

Installation	Individual or in line; suspended mounting with suspension set
Accessories	1-, 2- , 3- and 4- lamp luminaires delivered incl. suspension sets:
	- ZPS460 SMT1: suspension set single wire, triangle version 1 (1-, 2- and 3-lamp)
	- ZPS460 SMT2: suspension set single wire, triangle version 2, incl. mains connection (1-, 2- and 3-lamp)
	- ZPS460 SMTT: suspension set single wire, triangle for T-profile (1-, 2- and 3-lamp)
	- ZPS460 SMS: suspension set double wires, incl. mains connection (2- and 3-lamp)
	- ZPS460 SM4: suspension set 4 single wires (4-lamp)
	1-, 2- and 3-lamp light lines, straight and L-shape to create with ZPS460 CP/CPL coupling pieces; luminaires line-end (LE) and line-feature (LF) are including connection and through-wiring
Remarks	Protection foil to protect the optic during installation
Main applications	Office, education, healthcare, recreation, retail, industry

SmartForm TPS460/462/464

Accessories



Optical cover remover

Ordercode 910403205603

© 2018 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.