



Savio – pure light

Savio TPS760 C

Featuring Philips' patented micro-lens optic technology, Savio is a complete luminaire range that offers the ideal combination of stylish design and optimum performance for both task and general lighting. Savio has an edge-to-edge lighting appearance with a uniform and comfortable brightness impression – a real 'surface of light'. The micro-lens optic consists of a single plate and is embedded in a housing made of high-quality natural anodized aluminum. Savio ensures optimum light distribution and full glare control in compliance with the latest office-lighting norm (EN 12464-1). Savio luminaires with Dynamic Lighting keep us feeling active by creating dynamic artificial light that varies over the course of the day or is set according to personal preference. Savio is available as suspended and surface-mounted.

Benefits

- Combines outstanding lighting performance, aesthetic appeal and architectural integration
- Edge-to-edge 'surface of light' effect with even, comfortable brightness
- Patented micro-lens optic for optimum light distribution and full glare control

Features

- Inspiring: edge-to-edge lighting appearance with a uniform and comfortable brightness impression, providing a real 'surface of light'
- Flexibility: suspended and surfaced versions offer a choice of direct or direct/indirect lighting distribution
- Comfort: optimum light distribution and full glare control thanks to micro-lens optic technology

Application

- Open plan office
- Meeting room
- Cell office
- Lounge

Specifications

Savio TPS760 C

Type	TCS760 (surface-mounted version)
	TPS760 (pendant, direct lighting version)
	TPS762 (pendant, direct 70% / indirect 30% lighting version)
Light source	Fluorescent: - 2 x MASTER TL5 / G5 / 14, 24, 28, 35, 49, 54 W
Lamp included	No
Ballast	Electronic, High Frequency 220-240 V / 50-60 Hz: - HF-Performer (HFP)
Optical cover	OLC micro-lens optic (AC-MLO)
Options	Euro fuse (FU) included

Connection	Push-in connector
Material	Housing: anodized aluminum
	Optical cover: PMMA (optional is polycarbonate)
	Rim: polycarbonate (translucent)
Installation	TCS760
	- Individual; screw mounting
	TPS760/762 - Individual or in line; suspended mounting with a set of two double steel-wire suspensions (SMS)

Versions




TPS762 C 2xTL5 HFP AC-MLO



TPS760 C 4xTL5 HFP AC-MLO

Product details



TPS760 AC-MLO surface view



TPS760 side view

Savio TPS760 C

Approval and Application

Mech. impact protection code	IK03
Ingress protection code	IP40

Operating and Electrical

Input Voltage	220 to 240 V
---------------	--------------

General Information

Protection class IEC	Safety class I
Optical cover/lens type	Acrylate micro-lens optic
Flammability mark	For mounting on normally flammable surfaces
Gear	HFP
Lamp family code	TL5

General Information

Order Code	Full Product Name	Lamp power	Number of light sources
911401005880	TPS760 C 2xTL5-28W HFP AC-MLO FU SMS	28 W	2 pcs
911401005980	TPS760 C 2xTL5-35W HFP AC-MLO FU SMS	35 W	2 pcs
911401006180	TPS762 C 2xTL5-28W HFP AC-MLO FU SMS	28 W	2 pcs
911401006280	TPS762 C 2xTL5-35W HFP AC-MLO FU SMS	35 W	2 pcs
911401006080	TPS760 C 4xTL5-14W HFP AC-MLO FU SM4	14 W	4 pcs
911401006380	TPS762 C 4xTL5-14W HFP AC-MLO FU SM4	14 W	4 pcs

