PHILIPS

Lighting



Halogen non-reflector lamps – high-quality light and easy to use

Halogen non-reflector

Halogen non-reflector lamps offer high-quality light and are easy to install, replace and operate. All halogen non-reflector lamps incorporate a distortion-free quartz bulb and a precise positioning of the mounted filament. These ensure optimal beam performance and consistent, high light output. A wide range of wattages is available for a broad variety of applications, including projection systems. In addition you get all the proven advantages of halogen technology such as a full spectrum and a color rendering index (CRI) of 100 – the same as natural light and the best that it can be. Halogen lamps also create a comfortable warm white light, and they maintain their lumen output, with almost no reduction, throughout their lifetime.

优点

- Optimal beam performance
- 100% Color Rendering Index (CRI)
- Constant light output throughout lifetime

特点

- Distortion-free, quartz bulb and precisely defined filament position
- Lamp replacement without adjustment
- XHP version with xenon gas for maximum light output
- Flat filament available

Halogen non-reflector

应用


- Studio, film, theatre and disco lighting
- Slide, overhead, profile and 8/16 mm film projectors
- Microscopes
- Optical equipment
- Slide and film viewers
- Surgery lamps
- Microfilm readers
- Dental lamps
- Spectrography

Versions







二维绘图




Product	D (max)	L (min)	L (max)	L	P (max)	P	P (min)	C (max)
7724 100W GY6.35 12V 1CT/10X10F	10.7 mm	29.65 mm	30.25 mm	30 mm	1.30 mm	1.25 mm	1.20 mm	44 mm
7158 150W G6.35 24V 1CT/10X10F	11.5 mm	31.5 mm	32.25 mm	32 mm	1.05 mm	1 mm	0.95 mm	50 mm
7027 50W G6.35 12V 1CT/ 10X10F	11.5 mm	29.75 mm	30.25 mm	30 mm	1.05 mm	1 mm	0.95 mm	44 mm
7748XHP 250W G6.35 24V 1CT/ 10X10F	12.5 mm	32.75 mm	33.25 mm	33 mm	1.05 mm	1 mm	0.95 mm	55 mm
7158XHP 150W G6.35 24V 1CT/10X10F	11.5 mm	31.5 mm	33.25 mm	33 mm	1.05 mm	1 mm	0.95 mm	50 mm
6550 150W G6.35 15V 1CT/ 10X10F	11.5 mm	29.75 mm	30.25 mm	30 mm	1.05 mm	1 mm	0.95 mm	44 mm
7023 100W GY6.35 12V 1CT/10X10F	11.5 mm	29.75 mm	30.25 mm	30 mm	1.30 mm	1.25 mm	1.20 mm	44 mm

Halogen non-reflector

二维绘图



Product	D (max)	L (max)	C (max)
7388 20W G4 6V 1CT/10X10F	9.5 mm	19.75 mm	31 mm
7387 10W G4 6V 1CT/10X10F	9.5 mm	19.75 mm	31 mm
6605 10W G4 6V 1CT/10X10F	9.5 mm	19.75 mm	31 mm
5761 30W G4 6V 1CT/10X10F	9.5 mm	19.75 mm	31 mm



Product	D (max)	L (min)	L (max)	L	P (max)	P	P (min)	C (max)
14531 360W G5.3 82V 1CT	11.5 mm	30.8 mm	32 mm	31.8 mm	1.65 mm	1.50 mm	1.47 mm	57 mm

基本資訊	
主要應用	Projection
照明科技	
顯色指數 (Nom)	100
機械和殼體	
燈泡材質	Quartz-UV Open

運作和電氣

Order Code	Full Product Name	電壓 (標稱)	功率 (額定)(標稱)
923870017103	7023 100W GY6.35 12V 1CT/10X10F	12 V	100 W
923872517103	7724 100W GY6.35 12V 1CT/10X10F	12 V	100 W
923870217103	7027 50W G6.35 12V 1CT/10X10F	12 V	50 W
923870520503	7158 150W G6.35 24V 1CT/10X10F	24 V	150 W
923870618503	6550 150W G6.35 15V 1CT/10X10F	15 V	150 W
924006520503	7748XHP 250W G6.35 24V 1CT/10X10F	24 V	250 W

Order Code	Full Product Name	電壓 (標稱)	功率 (額定)(標稱)
924031720503	7158XHP 150W G6.35 24V 1CT/10X10F	24 V	150 W
923873910103	6605 10W G4 6V 1CT/10X10F	6 V	10 W
923874510103	7387 10W G4 6V 1CT/10X10F	6 V	10 W
923874610103	7388 20W G4 6V 1CT/10X10F	6 V	20 W
923931110103	5761 30W G4 6V 1CT/10X10F	6 V	30 W
924041528894	14531 360W G5.3 82V 1CT	82 V	360 W

基本資訊

Order Code	Full Product Name	Ansi 代碼	接口	LIF 代碼	壽命 (故障率 50%) (標稱)	操作位置	Philips 代碼
923870017103	7023 100W GY6.35 12V 1CT/10X10F	FCR	GY6.35	A1/215	50 h	S90	7023
923872517103	7724 100W GY6.35 12V 1CT/10X10F	EVA	GY6.35	M28	2000 h	S90	7724
923870217103	7027 50W G6.35 12V 1CT/10X10F	BRL-BCD	G6.35	A1/220	50 h	S90	7027
923870520503	7158 150W G6.35 24V 1CT/10X10F	FCS	G6.35	A1/216	50 h	S90	7158

Halogen non-reflector

Order Code	Full Product Name	Ansi 代碼	接口	LIF 代碼	壽命 (故障率 50%) (標稱)	操作位置	Philips 代碼
923870618503	6550 150W G6.35 15V 1CT/10X10F	EVB-BRJ	G6.35	A1/234	50 h	S90	6550
924006520503	7748XHP 250W G6.35 24V 1CT/10X10F	EHJ	G6.35	A1/223	50 h	S90	7748XHP
924031720503	7158XHP 150W G6.35 24V 1CT/10X10F	FCS	G6.35	A1/216	40 h	S90	7158XHP
923873910103	6605 10W G4 6V 1CT/10X10F	-	G4	M42	2000 h	UNIVERSAL	6605
923874510103	7387 10W G4 6V 1CT/10X10F	ESA	G4	M29	100 h	S90	7387
923874610103	7388 20W G4 6V 1CT/10X10F	ESB	G4	M30	100 h	UNIVERSAL	7388
923931110103	5761 30W G4 6V 1CT/10X10F	-	G4	-	100 h	UNIVERSAL	5761
924041528894	14531 360W G5.3 82V 1CT	EYB	G5.3	-	75 h	S90	14531

照明科技

Order Code	Full Product Name	相關色溫 (標稱)	光通量 (標稱)	光通量 (額定) (標稱)
923870017103	7023 100W GY6.35 12V 1CT/10X10F	3450 K	-	3600 lm
923872517103	7724 100W GY6.35 12V 1CT/10X10F	3300 K	-	2800 lm
923870217103	7027 50W G6.35 12V 1CT/10X10F	3350 K	-	1600 lm
923870520503	7158 150W G6.35 24V 1CT/10X10F	3450 K	-	5200 lm
923870618503	6550 150W G6.35 15V 1CT/10X10F	3450 K	-	5600 lm

Order Code	Full Product Name	相關色溫 (標稱)	光通量 (標稱)	光通量 (額定) (標稱)
924006520503	7748XHP 250W G6.35 24V 1CT/10X10F	3550 K	-	10000 lm
924031720503	7158XHP 150W G6.35 24V 1CT/10X10F	3450 K	-	6000 lm
923873910103	6605 10W G4 6V 1CT/10X10F	2700 K	150 lm	-
923874510103	7387 10W G4 6V 1CT/10X10F	3200 K	200 lm	-
923874610103	7388 20W G4 6V 1CT/10X10F	3350 K	460 lm	-
923931110103	5761 30W G4 6V 1CT/10X10F	3200 K	765 lm	-
924041528894	14531 360W G5.3 82V 1CT	3300 K	-	10000 lm

機械和殼體

Order Code	Full Product Name	燈絲形狀
923870017103	7023 100W GY6.35 12V 1CT/10X10F	Flat
923872517103	7724 100W GY6.35 12V 1CT/10X10F	Flat
923870217103	7027 50W G6.35 12V 1CT/10X10F	Flat
923870520503	7158 150W G6.35 24V 1CT/10X10F	Flat
923870618503	6550 150W G6.35 15V 1CT/10X10F	Flat
924006520503	7748XHP 250W G6.35 24V 1CT/10X10F	Flat

Order Code	Full Product Name	燈絲形狀
924031720503	7158XHP 150W G6.35 24V 1CT/10X10F	Flat
923873910103	6605 10W G4 6V 1CT/10X10F	-
923874510103	7387 10W G4 6V 1CT/10X10F	-
923874610103	7388 20W G4 6V 1CT/10X10F	-
923931110103	5761 30W G4 6V 1CT/10X10F	-
924041528894	14531 360W G5.3 82V 1CT	Flat

© 2019 Signify Holding 保留一切權利。 Signify 不對本協議所含括資訊之準確性及完整性提供任何聲明或保證，對以此訊息為依據採取的任何行動亦概不負責。 除非 Signify 同意，本文件提及之資訊並非任何商業合約，亦不構成任何報價或合約任一部分。 其他所有商標均為 Signify Holding 或個別擁有人所有財產。

www.lighting.philips.com
2019, 五月 17 - 要更改的数据主题