



PAR56 and PAR 64 – picking out the smallest of details

PAR56 and PAR64

These self-contained spotlights are ideal for intensifying the visual experience in all kinds of clubs, that is because their accurate beam control picks out even the smallest of details even over long distances. This beam control makes the PAR 56 and PAR 64 excellent for long-range light projections. In addition, the universal burning feature provides complete flexibility of luminaires angle and position, while the front glass of the PAR56 provides thermal and physical protection. The result? Complete creative freedom to achieve the desired effect. Immediate re-strike also ensures instant resumption of entertainment after any power interruption.

Benefits

- Allows details to be picked out over long distances with good beam control
- Excellent for long-range light projections
- Provides thermal and physical protection
- Allows fullest flexibility of luminaire angle and position to obtain the desired effect
- Immediate re-strike after any power interruption

Features

- Self-contained spotlight
- Front glass
- Universal burning
- Hot restrike

Application

- Ideal for a wide range of performance and event lighting applications, for example in clubs, studios and theaters


PAR56 and PAR64

Versions



XPPR XPAR64 0002

Dimensional drawing



General Information	
Operating Position	UNIVERSAL
Controls and Dimming	
Dimmable	Yes

General Information

Order Code	Full Product Name	Cap-Base	Nominal lifetime
924783244204	PAR64 1000W 230V VNSP	GX16d	300 hour(s)
924783245504	PAR64 1000W 240V VNSP	GX16d	300 hour(s)
924783344204	PAR64 1000W 230V NSP	GX16d	300 hour(s)
924783345504	PAR64 1000W 240V NSP	GX16d	300 hour(s)

Light Technical

Order Code	Full Product Name	Beam Angle (Nom)	Correlated Color Temperature (Nom)
924783244204	PAR64 1000W 230V VNSP	11 degree(s)	3200 K
924783245504	PAR64 1000W 240V VNSP	11 degree(s)	3200 K
924783344204	PAR64 1000W 230V NSP	12 degree(s)	3200 K
924783345504	PAR64 1000W 240V NSP	12 degree(s)	3200 K
924783444204	PAR64 1000W 230V MFL	23 degree(s)	3200 K

Product	D (max)	C (max)
PAR56 300W 230V MFL	178 mm	127 mm
PAR64 1000W 230V MFL	204 mm	150 mm
PAR64 1000W 230V NSP	204 mm	150 mm
PAR64 1000W 230V VNSP	204 mm	150 mm
PAR64 1000W 240V MFL	204 mm	150 mm
PAR64 1000W 240V NSP	204 mm	150 mm
PAR64 1000W 240V VNSP	204 mm	150 mm
Par56 MFL 300W 240V GX16d.1CT/6	178 mm	127 mm

Order Code	Full Product Name	Cap-Base	Nominal lifetime
924783444204	PAR64 1000W 230V MFL	GX16D	300 hour(s)
924783445504	PAR64 1000W 240V MFL	GX16d	300 hour(s)
924783644204	PAR56 300W 230V MFL	GX16d	2.000 hour(s)
924783645504	Par56 MFL 300W 240V GX16d.1CT/6	GX16d	2.000 hour(s)

Order Code	Full Product Name	Beam Angle (Nom)	Correlated Color Temperature (Nom)
924783445504	PAR64 1000W 240V MFL	23 degree(s)	3200 K
924783644204	PAR56 300W 230V MFL	20 degree(s)	3000 K
924783645504	Par56 MFL 300W 240V GX16d.1CT/6	20 degree(s)	3000 K

PAR56 and PAR64

Operating and Electrical

Order Code	Full Product Name	Voltage (Nom)	Power Consumption
924783244204	PAR64 1000W 230V VNSP	230 V	1,000 W
924783245504	PAR64 1000W 240V VNSP	240 V	1,000 W
924783344204	PAR64 1000W 230V NSP	230 V	1,000 W
924783345504	PAR64 1000W 240V NSP	240 V	1,000 W
924783444204	PAR64 1000W 230V MFL	230 V	1,000 W

Order Code	Full Product Name	Voltage (Nom)	Power Consumption
924783445504	PAR64 1000W 240V MFL	240 V	1,000 W
924783644204	PAR56 300W 230V MFL	230 V	300 W
924783645504	Par56 MFL 300W 240V GX16d.1CT/6	240 V	300 W

Mechanical and Housing

Order Code	Full Product Name	Bulb Shape
924783244204	PAR64 1000W 230V VNSP	PAR64
924783245504	PAR64 1000W 240V VNSP	PAR64
924783344204	PAR64 1000W 230V NSP	PAR64
924783345504	PAR64 1000W 240V NSP	PAR64

Order Code	Full Product Name	Bulb Shape
924783444204	PAR64 1000W 230V MFL	PAR64
924783445504	PAR64 1000W 240V MFL	PAR64
924783644204	PAR56 300W 230V MFL	PAR56
924783645504	Par56 MFL 300W 240V GX16d.1CT/6	PAR56

