



Actinic BL TL(-K)/TL-D(-K) – optimized for Electronic Fly Killers

Actinic BL TL(-K)/TL-D(-K)

With an optimized spectrum matching the eye sensitivity of the housefly, Actinic BL TL(-K)/TL-D(-K)/TL-E/PL-S and PL-L lamps are perfect for attracting insects. They have virtually no UV-B output, and so are perfectly safe. What's more, with the lowest mercury content in the industry and being 100% lead-free, these lamps represent a very good environmental choice. Furthermore, the availability of a wide range of form factors (straight (T5, T8, T12), circular (TL-E) and compact (PL-S/PL-L)) and wattages enables you to make all kinds of designs for your electronic fly killers.

优点

- Perfectly matches the eye sensitivity of houseflies and in this way attracts more insects
- Safe for use
- Good environmental choice
- Design freedom

特点

- Emits long-wave UV-A radiation in the 350-400nm range
- UV-B/UV-A ratio less than 0.1 % (UV-B 280-315nm)
- 100% lead-free
- Low mercury content
- Wide power range

应用

- Insect traps, Electronic Fly Killers (EFKs)

Actinic BL TL(-K)/TL-D(-K)


安全提示

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Versions



二维绘图



Product
Actinic BL TL 6W/10 1FM/10X25CC
Actinic BL TL 11W/10
Actinic BL TL 8W/10 1FM/10X25CC

Product	D (max)	A (max)	B (max)	B (min)	C (max)
Actinic BL TL-D 15W/10 1SL/25	28 mm	437.4 mm	444.5 mm	442.1 mm	451.6 mm

Actinic BL TL(-K)/TL-D(-K)

基本信息

主要应用 Insect traps

照明科技

颜色代码 10

颜色名称 Actinic

紫外线

UV-B/UV-A (IEC) 0.2 %

应用

Order Code	Full Product Name	汞 (Hg) 含量 (标称)
928000501030	Actinic BL TL 6W/10 1FM/10X25CC	4.4 mg
928000601030	Actinic BL TL 11W/10	4.4 mg

Order Code	Full Product Name	汞 (Hg) 含量 (标称)
928001001030	Actinic BL TL 8W/10 1FM/10X25CC	4.4 mg
928024801029	Actinic BL TL-D 15W/10 1SL/25	5.0 mg

运营和电气

Order Code	Full Product Name	功率 (额定)		
		灯具电流 (标称)	电压 (标称)	(标称)
928000501030	Actinic BL TL 6W/10 1FM/10X25CC	0.16 A	42 V	6 W
928000601030	Actinic BL TL 11W/10	0.400 A	34 V	11.5 W
928001001030	Actinic BL TL 8W/10 1FM/10X25CC	0.145 A	56 V	7.1 W

Order Code	Full Product Name	功率 (额定)		
		灯具电流 (标称)	电压 (标称)	(标称)
928024801029	Actinic BL TL-D 15W/10 1SL/25	0.34 A	51 V	15 W

基本信息

Order Code	Full Product Name	50% 故障条件下的		
		底座	使用寿命 (标称)	有效寿命 (标称)
928000501030	Actinic BL TL 6W/10 1FM/10X25CC	G5	10000 h	5000 h
928000601030	Actinic BL TL 11W/10	G5	-	2000 h
928001001030	Actinic BL TL 8W/10 1FM/10X25CC	G5	10000 h	5000 h

Order Code	Full Product Name	50% 故障条件下的		
		底座	使用寿命 (标称)	有效寿命 (标称)
928024801029	Actinic BL TL-D 15W/10 1SL/25	G13	8000 h	5000 h

机械和壳体

Order Code	Full Product Name	灯泡外形
928000501030	Actinic BL TL 6W/10 1FM/10X25CC	T16
928000601030	Actinic BL TL 11W/10	T16

Order Code	Full Product Name	灯泡外形
928001001030	Actinic BL TL 8W/10 1FM/10X25CC	T16
928024801029	Actinic BL TL-D 15W/10 1SL/25	T26

紫外线

Order Code	Full Product Name	紫外线 A 辐射 100 小时 (IEC)
928000501030	Actinic BL TL 6W/10 1FM/10X25CC	1.4 W
928000601030	Actinic BL TL 11W/10	2.0 W

Order Code	Full Product Name	紫外线 A 辐射 100 小时 (IEC)
928001001030	Actinic BL TL 8W/10 1FM/10X25CC	1.60 W
928024801029	Actinic BL TL-D 15W/10 1SL/25	3.5 W

Actinic BL TL(-K)/TL-D(-K)

