



Coreline Bollard

Coreline Bollard

Coreline Bollard is a professional bollard that will guide people at night time and will integrate very well in most urban landscape thanks to its discreet design.

Benefits

- Comfortable light
- Easy to install
- Saves energy compared to conventional lamps

Features

- 1000lm system output
- 1m height
- IP65 / IK10
- Available in Warm White and Neutral White
- Available with symmetric and asymmetric optic
- Ground section anchor accessory

Application

- Open spaces: Parks, squares, playgrounds
- Foot and cycle paths
- Car parks

Specifications

Ambient Temperature	-40 to +50 °C
Main colour of the luminaire	Dark Grey
Driver	Power supply unit (PSU)
Initial correlated colour temperature	3000 K
Initial input power	12 W, 13 W
Initial LED luminaire efficacy	80, 85 lm/W

Initial luminous flux	1000 lm
Input frequency	50 or 60 Hz
Input voltage	220-240 V
Light source colour	Warm white
Light source replaceable	No
Optic	Asymmetrical, symmetrical
Optical cover	Polycarbonate

Coreline Bollard

Versions



LED Module 1000 lm

Accessories



Ordercode 38379400

Approval and application

Mech. impact protection code	IK10
Surge protection (common/differential)	6/8 kV

Controls and dimming

Dimmable	No
----------	----

General information

CE mark	Yes
Light source colour	Warm white
Optical cover/lens type	O
Driver included	Yes
Flammability mark	NO
Lamp family code	LED10
Light source replaceable	No
Number of gear units	1 unit
Number of light sources	1

Initial performance (IEC compliant)

Init. Corr. Colour Temperature	3000 K
Init. Colour rendering index	>80
Initial luminous flux	1000 lm

Light technical

Standard tilt angle side entry	-
Standard tilt angle post-top	-
Upward light output ratio	50

Mechanical and housing

Colour	Dark Grey
--------	-----------

General information

Order Code	Full Product Name	Luminaire light beam spread	Optic type
38375600	BCP155 LED100/WW PSU 220-240V A 7043	135°	Asymmetrical
38377000	BCP155 LED100/WW PSU 220-240V S 7043	360°	Symmetrical

