
PHILIPS Lighting



NM - adding a touch of originality to any project

Bracket (NM)

The NM mounting arm features a 2 3/8" O.D. (60 mm) extruded-aluminum tube bent at 180°, welded to a cast-aluminum pole adaptor. The mounting arm includes a castaluminum decorative spiral element welded to the arm. The luminaire adaptor will accept a luminaire equipped with Lumec's four-bolt mounting system. The aluminum central pole adaptor slip-fits 9" (229 mm) over a 4" (102 mm), 5" (127 mm) or 5 9/16" (141 mm) O.D. pole or tenon. ~LT~a href="http://www.lumec.com/Lumec3Dv3/home/index_en.php" target="_blank"~GT~~LT~b~GT~Lumec3D: Online 3D Configurator~LT~/b~GT~~LT~/ a~GT~

Benefits

• Decorative, yet durable

Features


- Available in a variety of mounting configurations
- EPA of 2.81

Application

- Bridges, Monuments, Facades
- Road and Street

Bracket (NM)

Versions





© 2018 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.

www.lighting.philips.com 2018, December 2 - data subject to change