PHILIPS Lighting



RTA50 - enhancing your project's unique style

Pole (RTA50)

Made from a 12 flute, mandrel-formed, aluminum tapered shaft 6" round (152 mm) welded to a decorative cast-aluminum base incorporating an anchor plate. After tapering, forming and welding, the entire shaft assembly is heat-treated to T6 temper. A maintenance opening is complete with decorative cast-aluminum cover in the same style as the pole and copper ground lug. ~LT~a href="http:// www.lumec.com/Lumec3Dv2/home/index_en.php" target="_blank"~GT~~LT~b~GT~Lumec3D: Online 3D Configurator~LT~/ b~GT~~LT~/a~GT~

Benefits

- Built to withstand harsh environmental conditions
- Superior corrosion resistance
- \cdot Optimal strength and durability

Features

- \cdot Round tapered fluted
- \cdot Aluminum construction
- Available in various heights ranging from 12' to 18'

Application

- Bridges, Monuments, Facades
- Road and Street

Pole (RTA50)

Versions



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2019, April 14 - data subject to change