## **PHILIPS** Lighting



# SM8 - enhancing your project's unique style

### Pole (SM8)

Made from a one-piece, 4" round (102 mm) high-tensile carbon steel shaft sealed by a rolled and flattened vertical weld seam and welded over and in a 8 5/8" round (219 mm) high-tensilecarbon-steel pole base. The assembly is welded to both the top and bottom of a steel anchor plate. A 4 1/2" by 10" (114 by 254 mm) maintenance opening is completewith cover and copper ground lug. ~LT~a href="http:// www.lumec.com/Lumec3Dv2/home/index\_en.php" target="\_blank"~GT~~LT~b~GT~Lumec3D: Online 3D Configurator~LT~/ b~GT~~LT~/a~GT~

#### Benefits

- $\cdot$  Built to withstand harsh environmental conditions
- Superior corrosion resistance
- $\cdot$  Optimal strength and durability

#### Features

- Round
- $\cdot$  Steel construction
- Available in various heights ranging from 8' to 20'

#### Application

- Bridges, Monuments, Facades
- $\cdot$  Road and Street

#### Pole (SM8)

#### Versions



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2019, April 14 - data subject to change