



FBX LED High Bay

36,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution

36,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution - 145 lm/W

The FBX LED High Bay is a compact and economical luminaire utilizing the latest in LED technology. With several lumen packages and optical distribution patterns available, the FBX offers exceptional lighting in mid to high ceiling applications. Save energy without straining your project budget or sacrificing your light output.

Product data

General information	
Lamp Source Code	LED
Colour Temperature	4000 K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended
Number Of Pieces	1
Operating and electrical	
Voltages	120/208/240/277/347/480/UNIV V
Luminaire Input Watts	255
Conduit Connection	7/8 inch knockout
Mechanical and housing	
Fixture Size	2 ft x 4 ft
Enclosure	Metal and Plastic

Approval and application	
Energy Certifications	DLC Standard
Initial performance (IEC compliant)	
Luminaire Lumens	36000
Efficacy	145 lm/W
Product data	
Order product name	36,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution
Order code	FBX36LL40-UNV
Material Nr. (12NC)	DAY00006240
Catalog Number	FBX36LL40-UNV
Catalog Number Description	36,000 Nominal Delivered Lumens, 4000K, 80 CRI, General Distribution