



# APX LED High Bay

**8,000 Nominal Delivered Lumens, 4000K, 80 CRI, Narrow Distribution, Frosted Acrylic Lens**

8,000 Nominal Delivered Lumens, 4000K, 80 CRI, Narrow Distribution, Frosted Acrylic Lens - 114 lm/W

The APX LED High Bay provides durability and high performance for your customer's demanding environments. The APX can be specified for many areas requiring a sealed luminaire, such as laboratories, food processing, parking areas, and other industrial applications. The rugged housing and clear or frosted lens options combine for durable and effective lighting that is also comfortable for the occupants. LED technology provides efficiency, long life, and reduces energy costs.

## Product data

General information	
Lamp Source Code	LED
Colour Temperature	4000 K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended
Operating and electrical	
Voltages	120/208/240/277/347/480/UNIV V
Luminaire Input Watts	76
Mechanical and housing	
Shape	Rectangular
Approval and application	
Energy Certifications	DLC Standard National Sanitation Foundation

Initial performance (IEC compliant)	
Luminaire Lumens	8000
Efficacy	114 lm/W
Product data	
Order product name	8,000 Nominal Delivered Lumens, 4000K, 80 CRI, Narrow Distribution, Frosted Acrylic Lens
Order code	APX08LL40-UNV-N-LFA
Material Nr. (12NC)	DAY00008450
Catalog Number	APX08LL40-UNV-N-LFA
Catalog Number Description	8,000 Nominal Delivered Lumens, 4000K, 80 CRI, Narrow Distribution, Frosted Acrylic Lens

## APX LED High Bay

