



# FBX LED High Bay

**45,000 Nominal Delivered Lumens, 4000K, 80 CRI, Wide Distribution, Frosted Ribbed Lens**

45,000 Nominal Delivered Lumens, 4000K, 80 CRI, Wide Distribution, Frosted Ribbed Lens

The FBX LED High Bay is a compact and economical luminaire utilizing the latest in LED technology. With several lumen packages and optical distribution patterns available, the FBX offers exceptional lighting in mid to high ceiling applications. Save energy without straining your project budget or sacrificing your light output.

## Product data

General Information	
Lamp Source Code	LED
Colour Temperature	4000 K
CRI	80
Photometric Distribution Type	Direct
Mounting	Suspended
Operating and Electrical	
Voltages	120/208/240/277/347/480/UNIV V
Luminaire Input Watts	315
Mechanical and Housing	
Fixture Size	2 ft x 4 ft
Shape	Rectangular
Approval and Application	
Energy Certifications	DLC Standard

Initial Performance (IEC Compliant)	
Luminaire Lumens	45000
Product Data	
Order product name	45,000 Nominal Delivered Lumens, 4000K, 80 CRI, Wide Distribution, Frosted Ribbed Lens
Order code	FBX45LL40-UNV-W-LFR
Material Nr. (12NC)	DAY00008815
Catalog Number	FBX45LL40-UNV-W-LFR
Catalog Number Description	45,000 Nominal Delivered Lumens, 4000K, 80 CRI, Wide Distribution, Frosted Ribbed Lens