



ConTempo 150-250-350

RVP250 MHN-TD150W IC 220V-50Hz S SP

MHN-TD, 150 W, Symmetrical

The Contempo floodlight has a registered design that blends well with contemporary outdoor environments. It has a rugged pressure die-casted aluminum housing with corrosion resistant powder coating. Contempo also features an integrated energy saving copper ballast, electronic semi-parallel ignitor and capacitor. The unit has passed rigorous tests for dust and water ingress protection.

Product data

General Information	
Lamp family code	MHN-TD
Cap-Base	R7S [R7s]
Gear	CONV [Conventional]
Light Technical	
Number of light sources	1
Optic type outdoor	Symmetrical
Operating and Electrical	
Input Voltage	220 V
Line Frequency	50 Hz
Power Consumption	150 W

Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Product Data	
Order product name	RVP250 MHN-TD150W IC 220V-50Hz S SP
Full product name	RVP250 MHN-TD150W IC 220V-50Hz S SP
Full product code	910401648280
Order code	910401648280
Material Nr. (12NC)	910401648280
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

Datasheet, 2023, April 29 data subject to change

ConTempo 150-250-350

Dimensional drawing



