



# Cabana2 BY150P

## **BY150P 1xSON250W IC IP65**

Cabana 2, 1, SON, 250 W, Dust penetration-protected, jet-proof

Cabana 2 is a functional high-bay indoor luminaire for high-intensity discharge lamps. It is supplied with a reflector, which can be attached to the unit without screws by means of an ingenious bayonet construction. The innovative external beam regulator enables easy lamp adjustment (narrow or wide beam) at the installation site. The external connector means the electrical connection can be made without opening the unit. Two versions are available: the standard version for SON and HPI-P lamps, and a round version for CDM-TMW lamps.

#### **Product data**

| General Information                |   |
|------------------------------------|---|
| Lamp family code                   | SON [SON]                                   |
| Cap-Base                           | E40 [E40]                                   |
| Light source replaceable           | Yes   |
| Gear                               | CONV [Conventional]                         |
| Driver included                    | Yes   |
| Product family code                | BY150P [Cabana 2]                           |
| CE mark                            | Yes   |
| Flammability mark                  | For mounting on normally flammable surfaces |
| ENEC mark                          | -   |
| Glow-wire test                     | Temperature 650 °C, duration 5 s            |
|                                    |   |
| Light Technical                    |   |
| Correlated Color Temperature (Nom) | 2000 K                                      |
| Number of light sources            | 1   |
| Light source color                 | 220 gold                                    |
|                                    |   |

| Operating and Electrical  |                          |
|---------------------------|--------------------------|
| Input Voltage             | 230 V (default) or 240 V |
| Line Frequency            | 50 Hz                    |
| Power Consumption         | 250 W                    |
| Connection                | Push-in connector 3-pole |
|                           |                          |
| Temperature               |                          |
| Ambient temperature range | -15 to +35 °C            |
|                           |                          |
| Controls and Dimming      |                          |
| Dimmable                  | No                       |
|                           |                          |
| Mechanical and Housing    |                          |
| Housing Material          | Aluminum                 |
| Reflector material        | Aluminum                 |
| Optical cover material    | Glass                    |
| Housing Color             | Black                    |
|                           |                          |


Datasheet, 2023, September 4 data subject to change

# Cabana2 BY150P

| Approval and Application      |  |
|-------------------------------|--|
| Ingress protection code       | IP65 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code  | IK08 [5 J vandal-protected]                  |
| Protection class IEC          | Safety class I                               |
|                               |  |
| Application Conditions        |  |
| Suitable for random switching | Not applicable                               |
|                               |  |
| Product Data                  |  |
| Order product name            | BY150P 1xSON250W IC IP65                     |

| Full product name               | BY150P 1xSON250W IC IP65 |
|---------------------------------|--------------------------|
| Full product code               | 871829105234000          |
| Order code                      | 910402495412             |
| Material Nr. (12NC)             | 910402495412             |
| Numerator - Quantity Per Pack   | 1                        |
| EAN/UPC - Product/Case          | 8718291052340            |
| Numerator - Packs per outer box | 1                        |
| EAN/UPC - Case                  | 8718291052340            |
|                                 |                          |

## Dimensional drawing





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.