



# **ProLux TPS550 C**

## TPS550 2xTL5-54W HFP NB W3

2, TL5, 54 W, HF Performer, Narrow beam, Plug-in connector 3-pole Wieland/Adels compatible

In industry, the bottom line is affected by a whole host of factors — worker productivity, running costs and maintenance, to name just a few. In today's economic environment, with margins under pressure, all businesses operating high-bay facilities are faced with the pressing need to save energy. Our ProLux high-bay solution is a direct replacement for current HID high-bay systems and enables significant energy savings. The combination of robust housing, high-reflectance material and specially designed reflector add up to a high-efficiency luminiare that can help drive profitability by improving energy efficiency.

#### **Product data**

General Information	
Lamp family code	TL5 [TL5]
Gear	HFP [HF Performer]
Light Technical	
Number of light sources	2
Optic type	Narrow beam
Operating and Electrical	
Input Voltage	220 to 240 V
Power Consumption	54 W
Connection	Plug-in connector 3-pole Wieland/Adels compatible

Mechanical and Housing	
Housing Color	White
Product Data	
Order product name	TPS550 2xTL5-54W HFP NB W3
Full product name	TPS550 2xTL5-54W HFP NB W3
Full product code	910403630513
Order code	910403630513
Material Nr. (12NC)	910403630513
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

Datasheet, 2023, October 24 data subject to change

# **ProLux TPS550 C**

## Dimensional drawing



