



ProLux TPS550 C

TPS550 4XTL5-28W EBP NB

4, TL5, 28 W, Electronic Primalume, Narrow beam

In industry, the bottom line is affected by a whole host of factors – worker productivity, running costs and maintenance, to name just a few. In today's economic environment, with margins under pressure, all businesses operating high-bay facilities are faced with the pressing need to save energy. Our ProLux high-bay solution is a direct replacement for current HID high-bay systems and enables significant energy savings. The combination of robust housing, high-reflectance material and specially designed reflector add up to a high-efficiency luminaire that can help drive profitability by improving energy efficiency.

Product data

General Information	
Lamp family code	TL5 [TL5]
Gear	EBP [Electronic Primalume]
Flammability mark	For mounting on normally flammable surfaces
Light Technical	
Number of light sources	4
Optic type	Narrow beam
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Power Consumption	28 W
Approval and Application	
Ingress protection code	IP20 [Finger-protected]

Mech. impact protection code	IK03 [0.3 J]
Protection class IEC	Safety class I
Product Data	
Order product name	TPS550 4XTL5-28W EBP NB
Full product name	TPS550 4XTL5-28W EBP NB
Full product code	910403630525
Order code	910403630525
Material Nr. (12NC)	910403630525
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

ProLux TPS550 C

Dimensional drawing

