



# **ProLux TPS550 C**

## TPS550 6xTL5-54W HFR WB W3

6, TL5, 54 W, HF Regulator, Wide beam, Plug-in connector 3-pole Wieland/Adels compatible

In industry, the bottom line is affected by a whole host of factors — worker productivity, running costs and maintenance, to name just a few. In today's economic environment, with margins under pressure, all businesses operating high-bay facilities are faced with the pressing need to save energy. Our ProLux high-bay solution is a direct replacement for current HID high-bay systems and enables significant energy savings. The combination of robust housing, high-reflectance material and specially designed reflector add up to a high-efficiency luminiare that can help drive profitability by improving energy efficiency.

#### Product data


General Information	
Lamp family code	TL5 [TL5]
Gear	HFR [HF Regulator]
Light Technical	
Number of light sources	6
Optic type	Wide beam
Operating and Electrical	
Input Voltage	220 to 240 V
Power Consumption	54 W
Connection	Plug-in connector 3-pole Wieland/Adels compatible

Mechanical and Housing	
Housing Color	White
Product Data	
Order product name	TPS550 6xTL5-54W HFR WB W3
Full product name	TPS550 6xTL5-54W HFR WB W3
Full product code	910403630533
Order code	910403630533
Material Nr. (12NC)	910403630533
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

Datasheet, 2023, September 4 data subject to change

# ProLux TPS550 C

## Dimensional drawing





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.