



ProLux TPS550 C

TPS550 2XTL5-28W EBP NB

2, TL5, 28 W, Electronic Primalume, Narrow beam

In industry, the bottom line is affected by a whole host of factors – worker productivity, running costs and maintenance, to name just a few. In today's economic environment, with margins under pressure, all businesses operating high-bay facilities are faced with the pressing need to save energy. Our ProLux high-bay solution is a direct replacement for current HID high-bay systems and enables significant energy savings. The combination of robust housing, high-reflectance material and specially designed reflector add up to a high-efficiency luminaire that can help drive profitability by improving energy efficiency.

Product data

General Information	
Lamp family code	TL5 [TL5]
Gear	EBP [Electronic Primalume]
Light Technical	
Number of light sources	2
Optic type	Narrow beam
Operating and Electrical	
Input Voltage	220 to 240 V
Power Consumption	28 W
Mechanical and Housing	
Housing Color	White

Product Data	
Order product name	TPS550 2XTL5-28W EBP NB
Full product name	TPS550 2XTL5-28W EBP NB
Full product code	910403630550
Order code	910403630550
Material Nr. (12NC)	910403630550
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

ProLux TPS550 C

Dimensional drawing

