



OptiFlood Mini MVP504

MVP504 CDM-TD70W/942 EB II A GR

OptiFlood, MASTERColour CDM-TD, 70 W, Electronic, Asymmetrical

Philips has a long tradition of excellence in environmentally friendly asymmetric floodlighting systems for sports and general area lighting as well as architectural applications. OptiFlood's extremely efficient, best-in-class optical system provides an accurately controlled light distribution – total light cut-off above the horizontal and a peak beam intensity at high angles – keeping obtrusive light to a minimum. Both the MVP504 and MVP506 versions are available with two types of reflector – asymmetric or road-lighting POT optics – for flexibility in application. They can also accommodate CosmoPolis metal-halide lamps for good color rendering, high-pressure sodium lamps for economical operation, and MASTERColour CDM Elite MW lamps for highly efficient lighting with longer-lasting white light. OptiFlood is also available in a LED version (BVP506). With its compact shape and aesthetically pleasing design, OptiFlood can be used in applications where design and appearance are just as important as technical performance. In the design, attention has also been focused on the detailing. This has led to integrated 'hidden' hinges, angle adjustment designed as part of the body and a mounting bracket angled to allow more aesthetic integration onto columns.

Product data

General Information			
Lamp family code	CDM-TD [MASTERColour CDM-TD]	CE mark	Yes
Gear	EB [Electronic]	ENEC mark	-
Product family code	MVP504 [OptiFlood]	Light Technical	
Embedded control	-	Number of light sources	1

OptiFlood Mini MVP504

Light source color	942 neutral white
Optical cover type	Clear glass
Optic type outdoor	Asymmetrical

Operating and Electrical

Input Voltage	220 to 240 V
Power Consumption	70 W

Mechanical and Housing

Housing Color	Grey
---------------	------

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]

Protection class IEC	Safety class II
----------------------	-----------------

Product Data

Order product name	MVP504 CDM-TD70W/942 EB II A GR
Full product name	MVP504 CDM-TD70W/942 EB II A GR
Full product code	872790029318000
Order code	29318000
Material Nr. (12NC)	910403764512
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8727900293180
Numerator - Packs per outer box	1
EAN/UPC - Case	8727900293180

Dimensional drawing

