



# Europa 2

## FBS120 2XPL-C/4P26W/830 HF-H PG CCE

EUROPA 2, 2, MASTER PL-C 4 Pin, 26 W, 830 warm white, Electronic high-frequency in external gear box (HF), Protection glass, Cable with CEE 7 plug 3-pole

Europa 2 is a fixed recessed downlight for compact fluorescent PL-C lamps with highly efficient optics and automatic fixing clips for quick and easy installation. These downlights are available in two formats and can be fitted with a prismatic light control panel, opal cover, clear front panel or glare-control louver. Europa 2 is available in a ready-to-install kit version.

#### **Product data**

| General Information     |  |
|-------------------------|--|
| Lamp family code        | PL-C/4P [MASTER PL-C 4 Pin]                          |
| Gear                    | HF-H [Electronic high-frequency in external gear box |
|                         | (HF)]  |
| Product family code     | FBS120 [EUROPA 2]                                    |
| CE mark                 | Yes  |
| Flammability mark       | For mounting on normally flammable surfaces          |
| ENEC mark               | ENEC mark  |
| Glow-wire test          | Temperature 850 °C, duration 5 s                     |
|                         |  |
| Light Technical         |  |
| Number of light sources | 2  |
| Light source color      | 830 warm white                                       |
| Optic type              | -  |
| Optical cover type      | Protection glass                                     |
|                         |  |

| Operating and Electrical      |                                     |
|-------------------------------|-------------------------------------|
| Input Voltage                 | 220 to 240 V                        |
| Power Consumption             | 26 W                                |
| Connection                    | -                                   |
| Cable                         | Cable with CEE 7 plug 3-pole        |
|                               |                                     |
| Approval and Application      |                                     |
| Ingress protection code       | IP44 [Wire-protected, splash-proof] |
| Protection class IEC          | Safety class II                     |
|                               |                                     |
| Application Conditions        |                                     |
| Suitable for random switching | Not applicable                      |
|                               |                                     |
| Product Data                  |                                     |
| Order product name            | FBS120 2XPL-C/4P26W/830 HF-H PG CCE |
| Full product name             | FBS120 2XPL-C/4P26W/830 HF-H PG CCE |
| Full product code             | 871829108609300                     |
|                               |                                     |


Datasheet, 2023, September 4 data subject to change


## Europa 2

| Order code                    | 910500451732  |
|-------------------------------|---------------|
| Material Nr. (12NC)           | 910500451732  |
| Numerator - Quantity Per Pack | 1             |
| EAN/UPC - Product/Case        | 8718291086093 |

| Numerator - Packs per outer box 1 |               |  |
|-----------------------------------|---------------|--|
| EAN/UPC - Case                    | 8718291086093 |  |

### Dimensional drawing







© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.