



CoreLine Wall-mounted

WL120V LED12S/830 PSU EL3 GR

CoreLine Wall-mounted, LED module, system flux 1200 lm, 830 warm white, Power supply unit (On/Off), Emergency lighting 3 hours duration, Grey

Whether for a new building or renovation of an existing space, customers want lighting solutions that provide quality of light and substantial energy and maintenance savings. The new CoreLine Wall-mounted range of LED products can be used to replace traditional wall-mounted luminaires incorporating compact fluorescent lamps. The process of selecting, installing and maintaining is so easy – it's a simple switch.

Product data

General Information		Value ladder		Performance		
Lamp family code	LED12S [LED module, system flux 1200 lm]	Embedded control	-			
Light source replaceable	No	CE mark	Yes			
Number of gear units	1 unit	Warranty period	3 years + 2 years upon registration			
Driver included	Yes	Flammability mark	For mounting on normally flammable surfaces			
Remarks	*-Per Lighting Europe guidance paper	ENEC mark	ENEC mark			
	“Evaluating performance of LED based luminaires - January 2018”: statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore, the median useful life (B50) value also represents the B10 value.	Glow-wire test	Temperature 850 °C, duration 30 s			
		EU RoHS compliant	Yes			
Light Technical						
		Luminous Flux	1,200 lm			
		Correlated Color Temperature (Nom)	3000 K			
		Luminous Efficacy (rated) (Nom)	67 lm/W			

CoreLine Wall-mounted

Color rendering index (CRI)	80
Number of light sources	1
Beam angle of light source	120 degree(s)
Light source color	830 warm white
Optic type	Symmetrical
Luminaire light beam spread	180°

Operating and Electrical

Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Inrush current	22 A
Inrush time	0.32 ms
Power Consumption	18 W
Power Factor (Fraction)	0.95
Connection	Push-in connector and pull relief
Cable	-
Number of products on MCB of 16 A type B	15

Temperature

Ambient temperature range	0 to +25 °C
---------------------------	-------------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Constant light output	No

Mechanical and Housing

Housing Material	Composite materials
Reflector material	-
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Polyamide

Housing Color	Grey
Optical cover finish	Opal
Overall height	120 mm
Overall diameter	344 mm

Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK10 [20 J vandal-resistant]
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.43, 0.40) SDCM <3
Power consumption tolerance	+/-10%


Application Conditions

Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	No

Product Data

Order product name	WL120V LED12S/830 PSU EL3 GR
Full product name	WL120V LED12S/830 PSU EL3 GR
Full product code	871869624291900
Order code	24291900
Material Nr. (12NC)	910500454792
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696240946
Numerator - Packs per outer box	1
EAN/UPC - Case	8718696242919

Dimensional drawing



CoreLine Wall-mounted

