



CoreLine Wall-mounted

WL120V LED16S/830 PSU EL3 WH

CoreLine Wall-mounted, LED Module, system flux 1600 lm, 830 warm white, Power supply unit (On/Off), Emergency lighting 3 hours duration, White

Whether for a new building or renovation of an existing space, customers want lighting solutions that provide quality of light and substantial energy and maintenance savings. The new CoreLine Wall-mounted range of LED products can be used to replace traditional wall-mounted luminaires incorporating compact fluorescent lamps. The process of selecting, installing and maintaining is so easy – it's a simple switch.

Product data

General Information		Value ladder		Performance		
Lamp family code	LED16S [LED Module, system flux 1600 lm]	Embedded control	-			
Light source replaceable	No	CE mark	Yes			
Number of gear units	1 unit	Warranty period	3 years + 2 years upon registration			
Driver included	Yes	Flammability mark	For mounting on normally flammable surfaces			
Remarks	*-Per Lighting Europe guidance paper	ENEC mark	ENEC mark			
	“Evaluating performance of LED based	Glow-wire test	Temperature 850 °C, duration 30 s			
	luminaires – January 2018”: statistically there is	EU RoHS compliant	Yes			
	no relevant difference in lumen maintenance					
	between B50 and for example B10. Therefore,					
	the median useful life (B50) value also					
	represents the B10 value.					
Product family code	WL120V [CoreLine Wall-mounted]					
Lighting Technology	LED	Light Technical				
		Luminous Flux	1,600 lm			
		Correlated Color Temperature (Nom)	3000 K			
		Luminous Efficacy (rated) (Nom)	67 lm/W			

CoreLine Wall-mounted

Color rendering index (CRI)	80
Number of light sources	1
Beam angle of light source	120 degree(s)
Light source color	830 warm white
Optic type	Symmetrical
Luminaire light beam spread	180°

Operating and Electrical

Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Inrush current	22 A
Inrush time	0.32 ms
Power Consumption	24 W
Power Factor (Fraction)	0.95
Connection	Push-in connector and pull relief
Cable	-
Number of products on MCB of 16 A type B	15

Temperature

Ambient temperature range	0 to +25 °C
---------------------------	-------------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Constant light output	No

Mechanical and Housing

Housing Material	Composite materials
Reflector material	-
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Polyamide

Housing Color	White
Optical cover finish	Opal
Overall height	120 mm
Overall diameter	344 mm

Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK10 [20 J vandal-resistant]
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.43, 0.40) SDCM <3
Power consumption tolerance	+/-10%


Application Conditions

Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	No

Product Data

Order product name	WL120V LED16S/830 PSU EL3 WH
Full product name	WL120V LED16S/830 PSU EL3 WH
Full product code	871869624109700
Order code	24109700
Material Nr. (12NC)	910500454808
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696241097
Numerator - Packs per outer box	1
EAN/UPC - Case	8718696241097

Dimensional drawing



CoreLine Wall-mounted

