

# Maxos LED Performer

## 4MX900 491 LED40S/840 PSD-CLO NB WH

Maxos LED Performer, LED module, system flux 4000 lm, Power supply unit with DALI interface and constant light output, Narrow beam, Constant light output

Customers want to save energy and reduce cost compared to what they are used to with conventional lighting. At the same time, excellent lighting conditions are needed: in industrial environments, to guarantee safety and productivity; and in retail environments, to make the merchandise stand out and attract shoppers. Maxos LED Performer is an extremely flexible solution that delivers low energy consumption and excellent beam shaping at an attractive investment level.

### Product data

| General Information | |
|---|---|
| **Lamp family code** | LED40S [LED module, system flux 4000 lm] |
| **Light source replaceable** | No |
| **Number of gear units** | 1 unit |
| **Driver included** | Yes |
| **Remarks** | *-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore, the median useful life (B50) value also represents the B10 value. |
| **Service tag** | Yes |
| **Product family code** | 4MX900 [Maxos LED Performer] |
| **Lighting Technology** | LED |
| **Value ladder** | Performance |

| | |
|---|---|
| **Embedded control** | Constant light output |
| **CE mark** | Yes |
| **Warranty period** | 5 years |
| **Flammability mark** | - |
| **ENEC mark** | ENEC mark |
| **Glow-wire test** | Temperature 650 °C, duration 30 s |
| **EU RoHS compliant** | Yes |

| Light Technical | |
|---|---|
| **Luminous Flux** | 4,000 lm |
| **Correlated Color Temperature (Nom)** | 4000 K |
| **Luminous Efficacy (rated) (Nom)** | 133 lm/W |
| **Color rendering index (CRI)** | ≥80 |
| **Number of light sources** | 1 |
| **Beam angle of light source** | 120 degree(s) |
| **Light source color** | 840 neutral white |

# Maxos LED Performer

| | |
|---|---|
| **Optic type** | Narrow beam |
| **Luminaire light beam spread** | 34° |
| **Unified glare rating CEN** | Not applicable |

## Operating and Electrical

| | |
|---|---|
| **Input Voltage** | 220 to 240 V |
| **Line Frequency** | 50 to 60 Hz |
| **Initial CLO power consumption** | 23.6 W |
| **Average CLO power consumption** | 26.5 W |
| **Inrush current** | 21 A |
| **Inrush time** | 0.280 ms |
| **Power Consumption** | 30 W |
| **Power Factor (Fraction)** | 0.9 |
| **Connection** | Connection unit 5-pole |
| **Cable** | - |
| **Number of products on MCB of 16 A type B** | 24 |

## Temperature

| | |
|---|---|
| **Ambient temperature range** | -20 to +40 °C |

## Controls and Dimming

| | |
|---|---|
| **Dimmable** | Yes |
| **Driver/power unit/transformer** | Power supply unit with DALI interface and constant light output |
| **Control interface** | DALI |
| **Constant light output** | Yes |

## Mechanical and Housing

| | |
|---|---|
| **Housing Material** | Aluminum |
| **Reflector material** | - |
| **Optic material** | Polymethyl methacrylate |
| **Optical cover material** | Polymethyl methacrylate |
| **Fixation material** | Steel |
| **Housing Color** | White |
| **Optical cover finish** | Clear |
| **Overall length** | 1,479 mm |
| **Overall width** | 87 mm |
| **Overall height** | 82 mm |
| **Dimensions (Height x Width x Depth)** | 82 x 87 x 1479 mm |

## Approval and Application

| | |
|---|---|
| **Ingress protection code** | IP40 [Wire-protected] |
| **Mech. impact protection code** | IK02 [0.2 J standard] |
| **Protection class IEC** | Safety class I |

## Initial Performance (IEC Compliant)

| | |
|---|---|
| **Luminous flux tolerance** | +/-10% |
| **Initial chromaticity** | (0.38, 0.38) SDCM <3.5 |
| **Power consumption tolerance** | +/-10% |

## Over Time Performance (IEC Compliant)

| | |
|---|---|
| **Control gear failure rate at median useful life 50000 h** | 5 % |
| **Lumen maintenance at median useful life* 50000 h** | L80 |


## Application Conditions

| | |
|---|---|
| **Performance ambient temperature Tq** | 25 °C |
| **Maximum dim level** | 1% |
| **Suitable for random switching** | Not applicable |

## Product Data

| | |
|---|---|
| **Order product name** | 4MX900 491 LED40S/840 PSD-CLO NB WH |
| **Full product name** | 4MX900 491 LED40S/840 PSD-CLO NB WH |
| **Full product code** | 871869685350499 |
| **Order code** | 910500457792 |
| **Material Nr. (12NC)** | 910500457792 |
| **Numerator - Quantity Per Pack** | 1 |
| **EAN/UPC - Product/Case** | 8718696853504 |
| **Numerator - Packs per outer box** | 2 |
| **EAN/UPC - Case** | 8718696854792 |

## Dimensional drawing






© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.