

# CoreLine Downlight

## DN130B LED20S/830 PSU IP44 PI6 WH

CoreLine Downlight WH, LED Module, system flux 2000 lm, 830 warm white, Power supply unit (On/Off), Wire-protected, splash-proof, Push-in connector 6-pole, White

The CoreLine Downlight range of recessed luminaires is designed to replace CFL-ni/CFL-i based downlight luminaires. Their attractive TCO helps customers to make the switch to LED. These luminaires create a natural lighting effect for use in general lighting applications. They also deliver instant energy savings and have a much longer lifetime, creating a real value-for-money and environmentally friendly solution. They are easy to install thanks to their standard cut-out size and push-in connectors.

### Product data

General Information		Value ladder		Performance	
Lamp family code	LED20S [LED Module, system flux 2000 lm]	CE mark	Yes	Warranty period	5 years
Light source replaceable	No	Flammability mark	For mounting on normally flammable surfaces	ENEC mark	-
Number of gear units	Unit	Glow-wire test	Temperature 850 °C, duration 5 s	EU RoHS compliant	Yes
Driver included	Yes	Light Technical			
Remarks	* - According to the Lighting Europe guidance paper 'Evaluating performance of LED based luminaires – January 2018': statistically there is no relevant difference in lumen maintenance between the B50 and, for example, the B10. Therefore, the median useful life (B50) value also represents the B10 value.	Luminous Flux	2,100 lm	Correlated Colour Temperature	3000 K
Product family code	DN130B [CoreLine Downlight WH]	Luminous efficacy (rated) (nom.)	95 lm/W	Colour rendering index (CRI)	80
Lighting Technology	LED	Beam angle of light source	120 degree(s)		

## CoreLine Downlight

Light source colour	830 warm white
Optic type	Wide beam
Optical cover type	Acrylic bowl/cover frosted
Luminaire light beam spread	90°
Unified Glare Rating (CEN)	28

### Operating and Electrical

Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Inrush current	16 A
Inrush time	0.32 ms
Power Consumption	22 W
Power Factor (Fraction)	0.9
Connection	Push-in connector 6-pole
Cable	-
Number of products on MCB of 16 A type B	15

### Temperature

Ambient temperature range	-10 to +40 °C
---------------------------	---------------

### Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Constant light output	No

### Mechanical and Housing

Housing material	Polycarbonate
Reflector material	Polycarbonate
Optic material	Aluminium
Optical cover/lens material	Polycarbonate
Fixation material	Steel
Housing Colour	White
Optical cover/lens finish	Frosted
Overall height	109 mm

Overall diameter	216 mm
------------------	--------

### Approval and Application

Ingress protection code	IP44 [Wire-protected, splash-proof]
Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class I

### Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.43, 0.40) SDCM <5
Power consumption tolerance	+/-10%

### Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50,000 h	5 %
Lumen maintenance at median useful life* 50,000 h	L70


### Application Conditions

Performance ambient temperature Tq	25 °C
Suitable for random switching	Yes

### Product Data

Order product name	DN130B LED20S/830 PSU IP44 PI6 WH
Full product name	DN130B LED20S/830 PSU IP44 PI6 WH
Full EOC	871869687885900
Order code	87885900
Material no. (12 NC)	910500458082
SAP numerator – quantity per pack	1
EAN/UPC – Product/Case	8718696878859
Numerator – packs per outer box	1
EAN/UPC – Case	8718696878859

## Dimensional drawing



## CoreLine Downlight

