



ProAir

ST640T G2 LED20S/827 PSU NB10 WH

ProAir, Generation 2, LED Module, system flux 2000 lm, 827 warm white, Power supply unit (On/Off), Narrow beam angle 10°, White

Store designers want a spot that fits in with their store design. Visual merchandisers need the very best light quality and spots that are easily adjustable. And maintenance managers and green champions want to reduce energy consumption and maintenance costs. ProAir offers store designers a LED spot with an elegant and compact design that they can customize to suit their needs. It gives visual merchandisers great rendering of colors and whites and excellent color consistency, as well as well-defined, clean beams for maximum impact. All versions of ProAir offer low maintenance and energy consumption.

Product data

General Information			
Lamp family code	LED20S [LED Module, system flux 2000 lm]	CE mark	Yes
Light source replaceable	No	Warranty period	5 years
Number of gear units	1 unit	Flammability mark	For mounting on normally flammable surfaces
Driver included	Yes	ENEC mark	ENEC mark
Remarks	* -Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore, the median useful life (B50) value also represents the B10 value.	Glow-wire test	Temperature 650 °C, duration 5 s
Product family code	ST640T [ProAir]	EU RoHS compliant	Yes
Lighting Technology	LED	Light Technical	
		Luminous Flux	2,000 lm
		Correlated Color Temperature (Nom)	2700 K
		Luminous Efficacy (rated) (Nom)	91 lm/W
		Color rendering index (CRI)	≥80
		Number of light sources	1
		Beam angle of light source	120 degree(s)

Light source color	827 warm white
Optic type	Narrow beam angle 10°
Optical cover type	-
Luminaire light beam spread	10°

Operating and Electrical

Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Inrush current	18 A
Inrush time	0.250 ms
Power Consumption	22 W
Power Factor (Fraction)	0.9
Connection	-
Cable	-
Number of products on MCB of 16 A type	34

B

Temperature

Ambient temperature range	+10 to +40 °C
---------------------------	---------------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Control interface	-
Constant light output	No

Mechanical and Housing

Housing Material	Aluminum
Reflector material	Polycarbonate
Optic material	Polycarbonate
Optical cover material	Glass
Fixation material	-
Housing Color	White

Optical cover finish	Clear
Overall length	161 mm
Overall width	100 mm
Overall height	211 mm
Dimensions (Height x Width x Depth)	211 x 100 x 161 mm

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.46, 0.41) SDCM<3
Power consumption tolerance	+/-10%

Application Conditions

Performance ambient temperature Tq	25 °C
Suitable for random switching	Yes

Product Data

Order product name	ST640T G2 LED20S/827 PSU NB10 WH
Full product name	ST640T G2 LED20S/827 PSU NB10 WH
Full product code	871869687756200
Order code	910500458469
Material Nr. (12NC)	910500458469
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696877562
Numerator - Packs per outer box	1
EAN/UPC - Case	8718696877562

Dimensional drawing



