



TownGuide Performer

BDP101 LED30/740 DM PCF SI CLO-DDF1 76P

TOWNGUIDE PERF BOWL, LED GreenLine 3000 lm, Distribution medium, Polycarbonate bowl/cover frosted

The TownGuide Performer family consists of six recognizable yet modern shapes: Flat Cone, Bowl, Classic Cone, Classic, T and Tzero. All are available with a clear bowl. Except for Tzero, also a frosted bowl can be chosen. With an extensive range of lumen packages and a choice of light colors and operating lifetimes, it is easy to select the version that best suits your project's specific requirements. In addition, TownGuide Performer has a variety of control system options that can make it an integral part of your smart energy-reduction programs – from stand-alone LumiStep and DynaDimmer, SDU switch-dim control, through to seamless remote connectivity with CityTouch lighting management software. Installation is easy. Thanks to the bayonet whistle connector with integrated gland located in the spigot, the luminaire does not have to be opened at all for installation. Philips has made every effort to make the Total Cost of Ownership (TCO) of the luminaire as attractive as possible. And as TownGuide Performer is a dedicated LED luminaire, compatible with a variety of control systems, the energy and maintenance cost savings compared to conventional lighting are significant.

Product data

General Information		Value ladder	Performance
Lamp family code	GRN30 [LED GreenLine 3000 lm]	Embedded control	Constant light output and DynaDimmer fixed presets version 1
Light source replaceable	Yes	CE mark	Yes
Number of gear units	Unit	Warranty period	5 years
Driver included	Yes	Flammability mark	-
Photocell	-	ENEC mark	ENEC mark
Light source engine type	LED	Glow-wire test	Temperature 650 °C, duration 5 s
Product family code	BDP101 [TOWNGUIDE PERF BOWL]		
Lighting Technology	LED		

TownGuide Performer

EU RoHS compliant	No
-------------------	----

Light Technical

Upwards light output ratio	0.4
Luminous Flux	1,770 lm
Standard tilt angle post-top	0°
Standard tilt angle side entry	-
Correlated Colour Temperature	4000 K
Luminous efficacy (rated) (nom.)	86 lm/W
Colour rendering index (CRI)	70
Light source colour	840 neutral white
Optical cover type	Polycarbonate bowl/cover frosted
Luminaire light beam spread	53° x 71°
Optic type outdoor	Distribution medium

Operating and Electrical

Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Initial CLO power consumption	20.5 W
Average CLO power consumption	21 W
End CLO power consumption	21 W
Inrush current	22 A
Inrush time	0.29 ms
Power Consumption	21 W
Power Factor (Fraction)	0.96
Connection	Screw connection block 5-pole
Cable	-
Number of products on MCB of 16 A type B 20	

Temperature

Ambient temperature range	-40 to +35 °C
---------------------------	---------------

Controls and Dimming

Dimmable	Yes
Driver/power unit/transformer	Power supply unit with DynaDimmer and constant light output (integrated)
Control interface	-
Constant light output	Yes

Mechanical and Housing

Housing material	Aluminium
Reflector material	-
Optic material	Acrylate
Optical cover/lens material	Polycarbonate

Fixation material	Steel
Housing Colour	Silver
Mounting device	Post-top for diameter 76 mm
Optical cover/lens shape	Hemispherical flat
Optical cover/lens finish	Frosted
Overall height	293 mm
Overall diameter	570 mm
Effective projected area	0.095 m²
Parts colour	All parts coloured

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK10 [20 J vandal-resistant]
Surge Protection (Common/Differential)	Luminaire surge protection level up to 6 kV differential mode and 6 kV common mode
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-7%
Initial chromaticity	(0.38, 0.38) SDCM <5
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2

Over Time Performance (IEC Compliant)

Driver failure rate at 5,000 hours	0.5 %
------------------------------------	-------

Application Conditions

Maximum dim level	50%
-------------------	-----

Product Data

Order product name	BDP101 LED30/740 DM PCF SI CLO-DDF1 76P
Full product name	BDP101 LED30/740 DM PCF SI CLO-DDF1 76P
Full EOC	871869630245300
Order code	30245300
Material no. (12 NC)	910500991165
SAP numerator – quantity per pack	1
EAN/UPC — Product/Case	8718696302453
Numerator – packs per outer box	1
EAN/UPC – Case	8718696302453

TownGuide Performer

Dimensional drawing

