



TownGuide Performer

BDP100 LED20/740 DRW PCC SI CLO 62P

TOWNGUIDE PERF FLAT CONE, LED GreenLine 2000 lm,
Distribution residential wide, Polycarbonate bowl/cover clear,
Constant light output, Post-top for diameter 62 mm

The TownGuide Performer family consists of six recognizable, yet modern shapes: Flat Cone, Bowl, Classic Cone, Classic T, T and Tzero. Each luminaire has the option of a clear (PCC), translucent (PCTR) or frosted (PCF) bowl (except Tzero, which is only available with a clear bowl). With an extensive range of lumen packages, neutral white or warm white LED lights sources, and a range of dedicated optics for lower mounting heights, it's easy to select the version that best suits the specific requirements of your project. All this combined with a long life expectancy of 100,000 operating hours. In addition, TownGuide Performer has a variety of control system options that can make this luminaire an integral part of smart energy-reduction programs. This includes LumiStep, DynaDimmer, and LineSwitch stand-alone dim control, and Coded Mains group control, right up to seamless remote connectivity with Interact lighting management software. Installation is easy. Thanks to the bayonet whistle connector with integrated gland located in the spigot, there's no need to open the luminaire for installation. The Signify Service tag app offers direct access to all relevant data, ensuring maintenance is easy too. Philips has made every effort to make the Total Cost of Ownership (TCO) of the luminaire as attractive as possible. And as TownGuide Performer is a dedicated LED luminaire, compatible with a variety of control systems, there are significant energy and maintenance cost savings compared with conventional lighting.

Product data

General Information		Number of gear units	
Lamp family code	GRN20 [LED GreenLine 2000 lm]	Driver included	Yes
Light source replaceable	Yes	Photocell	-

TownGuide Performer

Light source engine type	LED
Product family code	BDP100 [TOWNGUIDE PERF FLAT CONE]
Lighting Technology	LED
Value ladder	Performance
Embedded control	Constant light output
CE mark	Yes
Warranty period	5 years
Flammability mark	-
ENEC mark	ENEC mark
Glow-wire test	Temperature 650 °C, duration 5 s
EU RoHS compliant	No

Light Technical

Upward light output ratio	0.4
Luminous Flux	1,360 lm
Standard tilt angle posttop	0°
Standard tilt angle side entry	-
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	96 lm/W
Color rendering index (CRI)	70
Number of light sources	4
Light source color	840 neutral white
Optical cover type	Polycarbonate bowl/cover clear
Luminaire light beam spread	39° x 96°
Optic type outdoor	Distribution residential wide

Operating and Electrical

Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Initial CLO power consumption	14.2 W
Average CLO power consumption	14.4 W
End CLO power consumption	14.4 W
Inrush current	22 A
Inrush time	0.29 ms
Power Consumption	14.4 W
Power Factor (Fraction)	0.93
Connection	Screw connection block 5-pole
Cable	-
Number of products on MCB of 16 A type B	20

Temperature

Ambient temperature range	-40 to +35 °C
---------------------------	---------------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit regulating with constant light output
Control interface	-

Constant light output	Yes
-----------------------	-----

Mechanical and Housing

Housing Material	Aluminum
Reflector material	-
Optic material	Acrylate
Optical cover material	Polycarbonate
Fixation material	Steel
Housing Color	Silver
Mounting device	Post-top for diameter 62 mm
Optical cover shape	Conical flat
Optical cover finish	Clear
Overall height	209 mm
Overall diameter	570 mm
Effective projected area	0.051 m²
Parts color	All parts colored

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK10 [20 J vandal-resistant]
Surge Protection (Common/Differential)	Luminaire surge protection level until 6 kV differential mode and 6 kV common mode
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-7%
Initial chromaticity	(0.38, 0.38) SDCM <5
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2

Over Time Performance (IEC Compliant)

Driver failure rate at 5000 h	0.5 %
-------------------------------	-------

Application Conditions

Maximum dim level	Not applicable
-------------------	----------------

Product Data

Order product name	BDP100 LED20/740 DRW PCC SI CLO 62P
Full product name	BDP100 LED20/740 DRW PCC SI CLO 62P
Full product code	871869632926900
Order code	910500991241
Material Nr. (12NC)	910500991241
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696329269
Numerator - Packs per outer box	1
EAN/UPC - Case	8718696329269

TownGuide Performer

Dimensional drawing

