# **PHILIPS** Lighting



# **SmartForm TBS460**

# TBS460 2x28W/840 HFP C8-VH W IP SC

SmartForm recessed modular, 2, 28 W, 840 neutral white, HF Performer, High-gloss optic 3D micro-lamellae very high reflectance, Plug-in connector 3-pole Wieland/Adels compatible

Reflecting Philips' drive for simplicity and sustainability, SmartForm recessed is a complete family of highly versatile modular and semi-modular luminaires. These luminaires are available with a choice of LED or MASTER TL5 light sources in square and rectangular versions. Designed to fit in a wide range of ceiling types, SmartForm can fulfill the majority of project requirements in most applications. Energy efficiency. As well as incorporating energy-efficient light sources and electronic ballasts, the SmartForm recessed family can be equipped with lighting controls. These include solutions for presence detection and daylight regulation (ActiLume) or daylight regulation only (Luxsense), thereby further reducing energy consumption (W/m<sup>2</sup> is very low). In this way, this Green Flagship range lowers overall cost of ownership as well as CO2 levels, making SmartForm an environmentally friendly choice. SmartForm recessed TBS460 - ultra-flat 'light beam'. SmartForm recessed TBS460 'light beam' luminaires are built around superior micro-optics and have a build-in height of a mere 45 mm, making them ideal for applications requiring very flat light fittings, e.g. refurbishment projects where ceiling space may be especially limited.

#### **Product data**

General Information		CE mark	Yes
Lamp family code	TL5 [TL5]	Flammability mark	For mounting on normally flammable surfaces
Gear	HFP [HF Performer]	ENEC mark	ENEC mark
Product family code	TBS460 [SmartForm recessed modular]	Glow-wire test	Temperature 850 °C, duration 5 s
Embedded control	-		

## **SmartForm TBS460**

Light Technical	
Number of light sources	2
Light source color	840 neutral white
Optic type	High-gloss optic 3D micro-lamellae very high
	reflectance
Optical cover type	-
Operating and Electrical	
Input Voltage	220 to 240 V
Power Consumption	28 W
Connection	Plug-in connector 3-pole Wieland/Adels compatible
Cable	-
Mechanical and Housing	
Housing Color	White
Overall length	1,197 mm


IP20 [Finger-protected]

Mech. impact protection code	IK02 [0.2 J standard]			
Protection class IEC	Safety class I			
Application Conditions				
Suitable for random switching	Not applicable			
Product Data				
Order product name	TBS460 2x28W/840 HFP C8-VH W IP SC			
Full product name	TBS460 2x28W/840 HFP C8-VH W IP SC			
Full product code	871150000256300			
Order code	910501773203			
Material Nr. (12NC)	910501773203			
Numerator - Quantity Per Pack	1			
EAN/UPC - Product/Case	8711500002563			
Numerator - Packs per outer box 1				
EAN/UPC - Case	8711500002563			

### Approval and Application

Ingress protection code

#### Dimensional drawing



Product	Α
TBS460 2x28W/840 HFP C8-VH W IP SC	1,197 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, October 9 - data subject to change