



SmartForm TBS460

TBS460 4x14W/840 HFP SQR M2 PIP IP

SmartForm recessed modular, 4, 14 W, 840 neutral white, HF Performer, Matt mirror ribbed lamellae louver, Push-in connector and pull relief

Reflecting Philips' drive for simplicity and sustainability, SmartForm recessed is a complete family of highly versatile modular and semi-modular luminaires. These luminaires are available with a choice of LED or MASTER TL5 light sources in square and rectangular versions. Designed to fit in a wide range of ceiling types, SmartForm can fulfill the majority of project requirements in most applications. Energy efficiency. As well as incorporating energy-efficient LED or MASTER TL5 light sources and a range of Philips electronic ballasts, the SmartForm recessed family can be equipped with lighting controls for presence detection and daylight regulation (ActiLume) or daylight regulation only (Luxsense) in order to reduce energy consumption (W/m² is very low). In this way, this Green Flagship range also reduces the overall cost of ownership as well as CO₂ levels, making SmartForm an environmentally friendly choice. SmartForm recessed TBS460 – ultra-flat 'light beam'. SmartForm recessed TBS460 'light beam' luminaires are built around superior micro-optics and have a build-in height of a mere 45 mm, making them ideal for applications requiring very flat light fittings, e.g. refurbishment projects where ceiling space may be especially limited.

Product data

General Information			
Lamp family code	TL5 [TL5]	Flammability mark	For mounting on normally flammable surfaces
Gear	HFP [HF Performer]	ENEC mark	ENEC mark
Product family code	TBS460 [SmartForm recessed modular]	Glow-wire test	Temperature 850 °C, duration 5 s
Embedded control	-	Light Technical	
CE mark	Yes	Number of light sources	4

SmartForm TBS460

Light source colour	840 neutral white
Optic type	Matt mirror ribbed lamellae louvre
Optical cover type	-

Operating and Electrical

Input Voltage	220 to 240 V
Power Consumption	14 W
Connection	Push-in connector and pull relief
Cable	-

Mechanical and Housing

Housing Colour	White
----------------	-------

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class I

Application Conditions

Suitable for random switching	Not applicable
-------------------------------	----------------

Product Data

Order product name	TBS460 4x14W/840 HFP SQR M2 PIP IP
Full product name	TBS460 4x14W/840 HFP SQR M2 PIP IP
Full EOC	871150000623300
Order code	00623300
Material no. (12 NC)	910501810103
SAP numerator – quantity per pack	1
EAN/UPC – Product/Case	8711500006233
Numerator – packs per outer box	1
EAN/UPC – Case	8711500006233

Dimensional drawing

