

SmartForm TBS411

TBS411 1x14W/840 HFP C8 PIP SC

SmartForm recessed semi-modular, 1, 14 W, 840 neutral white, HF Performer, High-gloss optic 3D micro-lamellae, Push-in connector and pull relief

Reflecting Philips' drive for simplicity and sustainability, SmartForm recessed is a complete family of highly versatile modular and semi-modular luminaires. These luminaires are available with a choice of LED or MASTER TL5 light sources in very small, slender versions. Designed to fit in a wide range of ceiling types, this complete family can fulfill the majority of project requirements in most applications. As well as incorporating energy-efficient light sources and electronic ballasts, the SmartForm recessed family can be equipped with lighting controls. These include solutions for presence detection and daylight regulation (ActiLume) or daylight regulation only (Luxsense), thereby further reducing energy consumption (W/m² is very low). In this way, this Green Flagship range lowers overall cost of ownership as well as CO2 levels, making SmartForm an environmentally friendly choice. These slender SmartForm recessed luminaires are designed for integration in variety of linear ceiling systems: exposed and concealed T-bar, plaster and the extended versions for bandraster ceilings. Micro-optics and covers (MLO-PC and Opal) in smallest concept, width 90 mm. Modular length 600, 900, 1200 and 1500 mm. To extend till 2400 mm.Micro-optics and covers in smallest concept with AIR function, width 100 mm. Modular length 600, 900, 1200 and 1500 mm. To extend till 2400 mm. Minioptics, 2-lamps, width 115 mm. Modular length 600, 900, 1200 and 1500 mm. To extend till 2400 mm.

Product data

General Information	
Lamp family code	TL5 [TL5]
Gear	HFP [HF Performer]

Feed-through wiring	-
Product family code	TBS411 [SmartForm recessed semi-modular]
Embedded control	-


Datasheet, 2023, October 9 data subject to change


SmartForm TBS411

CE mark	Yes
Glow-wire test	Temperature 850 °C, duration 5 s
Light Technical	
Number of light sources	1
Light source color	840 neutral white
Optic type	High-gloss optic 3D micro-lamellae
Optical cover type	-
Operating and Electrical	
Input Voltage	220 to 240 V
Power Consumption	14 W
Connection	Push-in connector and pull relief
Cable	-
Mechanical and Housing	
Housing Color	White
Overall length	597 mm
Overall width	90 mm
Overall height	98 mm
Dimensions (Height x Width x Depth)	98 x 90 x 597 mm

Approval and Application		
Ingress protection code	IP20 [Finger-protected]	
Mech. impact protection code	IKO2 [0.2 J standard]	
Protection class IEC	Safety class I	
Application Conditions		
Suitable for random switching	Not applicable	
Product Data		
Order product name	TBS411 1x14W/840 HFP C8 PIP SC	
Full product name	TBS411 1x14W/840 HFP C8 PIP SC	
Full product code	871794398541800	
Order code	910501874203	
Material Nr. (12NC)	910501874203	
Numerator - Quantity Per Pack	1	
EAN/UPC - Product/Case	8717943985418	
Numerator - Packs per outer box	1	
EAN/UPC - Case	8717943985418	

Dimensional drawing





Product	Α
TBS411 1x14W/840 HFP C8 PIP SC	597 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.