


SmartForm TBS411

TBS411 1x35W/840 HFP C8 PIP

SmartForm recessed semi-modular, 1, 35 W, 840 neutral white, HF Performer, High-gloss optic 3D micro-lamellae, Push-in connector and pull relief

Reflecting Philips' drive for simplicity and sustainability, SmartForm recessed is a complete family of highly versatile modular and semi-modular luminaires. These luminaires are available with a choice of LED or MASTER TL5 light sources in very small, slender versions. Designed to fit in a wide range of ceiling types, this complete family can fulfill the majority of project requirements in most applications. As well as incorporating energy-efficient light sources and electronic ballasts, the SmartForm recessed family can be equipped with lighting controls. These include solutions for presence detection and daylight regulation (ActiLume) or daylight regulation only (Luxsense), thereby further reducing energy consumption (W/m² is very low). In this way, this Green Flagship range lowers overall cost of ownership as well as CO2 levels, making SmartForm an environmentally friendly choice. These slender SmartForm recessed luminaires are designed for integration in variety of linear ceiling systems: exposed and concealed T-bar, plaster and the extended versions for bandraster ceilings. Micro-optics and covers (MLO-PC and Opal) in smallest concept, width 90 mm. Modular length 600, 900, 1200 and 1500 mm. To extend till 2400 mm.Micro-optics and covers in smallest concept with AIR function, width 100 mm. Modular length 600, 900, 1200 and 1500 mm. To extend till 2400 mm. Mini-optics, 2-lamps, width 115 mm. Modular length 600, 900, 1200 and 1500 mm. To extend till 2400 mm.

Product data

General Information	
Lamp family code	TL5 [TL5]
Gear	HFP [HF Performer]

Feed-through wiring	-
Product family code	TBS411 [SmartForm recessed semi-modular]
Embedded control	-

SmartForm TBS411

CE mark	Yes
Glow-wire test	Temperature 850 °C, duration 5 s

Light Technical

Number of light sources	1
Light source color	840 neutral white
Optic type	High-gloss optic 3D micro-lamellae
Optical cover type	-

Operating and Electrical

Input Voltage	220 to 240 V
Power Consumption	35 W
Connection	Push-in connector and pull relief
Cable	-

Mechanical and Housing

Housing Color	White
Overall length	1,497 mm

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK07 [2 J reinforced]
Protection class IEC	Safety class I


Application Conditions

Suitable for random switching	Not applicable

Product Data

Order product name	TBS411 1x35W/840 HFP C8 PIP
Full product name	TBS411 1x35W/840 HFP C8 PIP
Full product code	871794398649100
Order code	910501886103
Material Nr. (12NC)	910501886103
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8717943986491
Numerator - Packs per outer box	1
EAN/UPC - Case	8717943986491

Dimensional drawing



Product	A
TBS411 1x35W/840 HFP C8 PIP	1,497 mm

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.