



Cleanroom LED

CR434B LED88/830 PSD W60L60 AC-MLO PI

Led Cleanroom mod. 600 lay-in, LED Module 8800 lm, 830 warm white, Power supply unit with DALI interface, Acrylate micro-lens optic, Push-in connector 5-pole

Customers operating highly hygienic facilities require special IP65, easy-to-clean, dust-free luminaires that meet all lighting requirements and norms. Moreover, to ensure the integrity of these areas (and stay within budget), they also need to minimize costly downtime and maintenance. With the latest LED engine on board, this LED cleanroom luminaire represents the ideal solution, delivering market-leading energy performance – far beyond fluorescent solutions – over 50,000 hours of maintenance-free operation. This means extremely low operational cost over the total lifetime of the luminaire, and so an excellent financial return on investment. The luminaire's high colour rendering properties ensure the top class optical performance required in e.g clinical areas in hospitals.

Product data

General Information			
Lamp family code	LED88 [LED Module 8800 lm]		useful life (B50) value also represents the B10 value.
Cap base	- [-]	Product family code	CR434B [Led Cleanroom mod. 600 lay-in]
Light source replaceable	No	Lighting Technology	LED
Number of gear units	Unit	Value ladder	Specification
Driver included	Yes	CE mark	Yes
Remarks	*- According to the Lighting Europe guidance paper 'Evaluating performance of LED based luminaires – January 2018': statistically there is no relevant difference in lumen maintenance between the B50 and, for example, the B10. Therefore, the median		
		Warranty period	5 years
		Flammability mark	For mounting on normally flammable surfaces
		ENEC mark	-
		Glow-wire test	Temperature 850 °C, duration 5 s

Cleanroom LED

EU RoHS compliant	Yes
-------------------	-----

Light Technical

Luminous Flux	6,000 lm
Correlated Colour Temperature	3000 K
Luminous efficacy (rated) (nom.)	109 lm/W
Colour rendering index (CRI)	≥80
Light source colour	830 warm white
Optic type	-
Optical cover type	Acrylate micro-lens optic
Luminaire light beam spread	120°
Unified Glare Rating (CEN)	19

Operating and Electrical

Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Inrush current	4.5 A
Inrush time	1 ms
Power Consumption	56 W
Power Factor (Fraction)	0.95
Connection	Push-in connector 5-pole
Cable	-
Number of products on MCB of 16 A type B	24

Temperature

Ambient temperature range	-20 to +40 °C
---------------------------	---------------

Controls and Dimming

Dimmable	Yes
Driver/power unit/transformer	Power supply unit with DALI interface
Control interface	DALI
Constant light output	No

Mechanical and Housing

Housing material	Steel
Reflector material	Aluminium
Optic material	-
Optical cover/lens material	Acrylate
Fixation material	-
Housing Colour	White
Optical cover/lens finish	Textured

Overall length	596 mm
Overall width	596 mm
Overall height	74 mm
Dimensions (height x width x depth)	74 x 596 x 596 mm

Approval and Application

Ingress protection code	IP64/65 Dust penetration-protected, splashproof/Jet-proof
Mech. impact protection code	IK02/05
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.43, 0.40) SDCM <3
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50,000 h	5 %
Lumen maintenance at median useful life* 50,000 h	L80

Application Conditions

Performance ambient temperature Tq	25 °C
Maximum dim level	1%
Suitable for random switching	No

Product Data

Order product name	CR434B LED88/830 PSD W60L60 AC-MLO PI
Full product name	CR434B LED88/830 PSD W60L60 AC-MLO PI
Full EOC	871794391891100
Order code	91891100
Material no. (12 NC)	910501978203
SAP numerator – quantity per pack	1
EAN/UPC – Product/Case	8717943918911
Numerator – packs per outer box	1
EAN/UPC – Case	8717943918911

Cleanroom LED

Dimensional drawing

