



CitySoul

CGP431 SON-T100W K II OR FG GR SND 76P

CITY SOUL, SON-T, 100 W, Open CT-POT, Flat glass, Post-top for diameter 76 mm

CitySoul is a family of modular street-lighting luminaires featuring state-of-the-art lamp and gear technologies – including LED – and offering outstanding optical performance. Its classic design merges well with today's urban environment. The simple, flat, ellipsoidal form of the luminaire creates an elegant light-point. Suitable for side-entry, suspended or post-top installation, and with its adjustable beam and light trespass accessories, this versatile luminaire fits every application. CitySoul comes in two sizes, along with a complete range of dedicated masts and brackets.

Product data

General Information				
Lamp family code	SON-T [SON-T]			
Gear	CONV [Conventional]			
Photocell	-			
Product family code	CGP431 [CITY SOUL]			
Embedded control	-			
CE mark	Yes			
ENEC mark	ENEC mark			
Light Technical				
Number of light sources	1			
Optical cover type	Flat glass			
Optic type outdoor	Open CT-POT			
Operating and Electrical				
Input Voltage	230 V			

Power Consumption	100 W				
Mechanical and Housing					
Housing Color	Grey				
Mounting device	Post-top for diameter 76 mm				
Overall length	754 mm				
Overall width	480 mm				
Approval and Application					
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]				
Mech. impact protection code	IK08 [5 J vandal-protected]				
Protection class IEC	Safety class II				
Product Data					
Full product code	871155967981500				
Order product name	CGP431 SON-T100W K II OR FG GR SND 76P				


Datasheet, 2023, September 4 data subject to change

CitySoul


Order code	910502106318		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	1		
Material Nr. (12NC)	910502106318		
Full product name	CGP431 SON-T100W K II OR FG GR SND 76P		


EAN/UPC - Case	8711559679815
EAN/UPC - Product/Case	8711559679815

Dimensional drawing









Product	Α	В	С	D
CGP431 SON-T100W K II OR FG GR SND 76P	196 mm	620 mm	754 mm	480 mm

