



CitySoul

CGP430 CDO-TT70W K II FG GR SND 60S

CITY SOUL MINI, MASTER CityWhite CDO-TT, 70 W, Flat glass, Side-entry for diameter 60 mm

CitySoul is a family of modular street-lighting luminaires featuring state-of-the-art lamp and gear technologies – including LED – and offering outstanding optical performance. Its classic design merges well with today's urban environment. The simple, flat, ellipsoidal form of the luminaire creates an elegant light-point. Suitable for side-entry, suspended or post-top installation, and with its adjustable beam and light trespass accessories, this versatile luminaire fits every application. CitySoul comes in two sizes, along with a complete range of dedicated masts and brackets.

Product data

General Information				
Lamp family code	CDO-TT [MASTER CityWhite CDO-TT]			
Gear	CONV [Conventional]			
Photocell	-			
Product family code	CGP430 [CITY SOUL MINI]			
Embedded control	-			
CE mark	Yes			
ENEC mark	ENEC mark			
Light Technical				
Number of light sources	1			
Optical cover type	Flat glass			
Operating and Electrical				
Input Voltage	230 V			

Power Consumption	70 W			
Mechanical and Housing				
Housing Color	Grey			
Mounting device	Side-entry for diameter 60 mm			
Overall length	749 mm			
Overall width	400 mm			
Approval and Application				
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]			
Mech. impact protection code	IK09 [10 J]			
Protection class IEC	Safety class II			
Product Data				
Full product code	871155967955600			
Order product name	CGP430 CDO-TT70W K II FG GR SND 60S			


Datasheet, 2023, September 4 data subject to change


CitySoul


Order code	910502119818		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	1		
Material Nr. (12NC)	910502119818		
Full product name	CGP430 CDO-TT70W K II FG GR SND 60S		


EAN/UPC - Case	8711559679556
EAN/UPC - Product/Case	8711559679556


Dimensional drawing











Product	Α	В	С	D
CGP430 CDO-TT70W K II FG GR SND 60S	171 mm	510 mm	749 mm	400 mm

