



Iridium SGS253/453

SGS253 CDO-TT150W K I CR PC GR SND

IRIDIUM, MASTER CityWhite CDO-TT, 150 W, Closed CT-POT, Polycarbonate bowl/cover

Iridium is a family of road-lighting luminaires designed for three main applications – residential areas and minor roads, major roads and motorways. Its modularity allows the integration of optical or electronic components in order to adapt to the changing demands of road lighting, e.g. the growing demand for white light and controls. Iridium ensures low cost of ownership thanks to its superior optics, dimming and Telemanagement capability, and ease of installation and maintenance. The Iridium luminaire family includes MASTERColour CDM Elite MW, CosmoPolis and LED-enabled versions. It comes in four different sizes – for mounting heights from 3.5 to 12 meters – and is suitable for side-entry and post-top mounting. A full range of brackets ensures visual consistency between the column and the gently rounded luminaire, making Iridium a total solution. Each Iridium luminaire is fully recyclable; only the light source and driver have to be recycled separately.

Product data

| General Information | |
|-----------------------------|----------------------------------|
| Lamp family code | CDO-TT [MASTER CityWhite CDO-TT] |
| Gear | CONV [Conventional] |
| Photocell | - |
| Product family code | SGS253 [IRIDIUM] |
| Embedded control | - |
| CE mark | Yes |
| ENEC mark | ENEC mark |
| | |
| Light Technical | |
| Standard tilt angle posttop | 5° |
| | |

| Standard tilt angle side entry | 5° |
|--------------------------------|--------------------------|
| Number of light sources | 1 |
| Optical cover type | Polycarbonate bowl/cover |
| Optic type outdoor | Closed CT-POT |
| | |
| Operating and Electrical | |
| Input Voltage | 230 V |
| Power Consumption | 150 W |
| | |
| Mechanical and Housing | |
| Housing Color | Grey |
| | |

Datasheet, 2023, September 4 data subject to change


Iridium SGS253/453

| 289 mm |
|--|
| - |
| |
| |
| IP66 [Dust penetration-protected, jet-proof] |
| IK08 [5 J vandal-protected] |
| Safety class I |
| |
| |
| SGS253 CDO-TT150W K I CR PC GR SND |
| |

| Full product name | SGS253 CDO-TT150W K I CR PC GR SND | |
|---------------------------------|------------------------------------|--|
| Full product code | 871155984461900 | |
| Order code | 910502134318 | |
| Material Nr. (12NC) | 910502134318 | |
| Numerator - Quantity Per Pack | 1 | |
| EAN/UPC - Product/Case | 8711559844619 | |
| Numerator - Packs per outer box | 1 | |
| EAN/UPC - Case | 8711559844619 | |
| | | |


Dimensional drawing













| Product | Α |
|------------------------------------|--------|
| SGS253 CDO-TT150W K I CR PC GR SND | 289 mm |



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.