



CitySoul

CGP431 SON-T50W K II OR FG GR SND 76P

CITY SOUL, SON-T, 50 W, Open CT-POT, Flat glass, Post-top for diameter 76 mm

CitySoul is a family of modular street-lighting luminaires featuring state-of-the-art lamp and gear technologies – including LED – and offering outstanding optical performance. Its classic design merges well with today's urban environment. The simple, flat, ellipsoidal form of the luminaire creates an elegant light-point. Suitable for side-entry, suspended or post-top installation, and with its adjustable beam and light trespass accessories, this versatile luminaire fits every application. CitySoul comes in two sizes, along with a complete range of dedicated masts and brackets.

Product data

General Information			
Lamp family code	SON-T [SON-T]		
Gear	CONV [Conventional]		
Photocell	-		
Product family code	CGP431 [CITY SOUL]		
Embedded control	-		
CE mark	Yes		
ENEC mark	ENEC mark		
Light Technical			
Number of light sources	1		
Optical cover type	Flat glass		
Optic type outdoor	Open CT-POT		
Operating and Electrical			
Input Voltage	230 V		

Power Consumption	50 W			
Mechanical and Housing				
Housing Color	Grey			
Mounting device	Post-top for diameter 76 mm			
Overall length	754 mm			
Overall width	480 mm			
Approval and Application				
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]			
Mech. impact protection code	IK08 [5 J vandal-protected]			
Protection class IEC	Safety class II			
Product Data				
Full product code	871155947892000			
Order product name	CGP431 SON-T50W K II OR FG GR SND 76P			


Datasheet, 2023, September 4 data subject to change

CitySoul


Order code	910502207018		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	1		
Material Nr. (12NC)	910502207018		
Full product name	CGP431 SON-T50W K II OR FG GR SND 76P		


EAN/UPC - Case	8711559478920
EAN/UPC - Product/Case	8711559478920

Dimensional drawing









Product	Α	В	С	D
CGP431 SON-T50W K II OR FG GR SND 76P	196 mm	620 mm	754 mm	480 mm

