



CitySoul

CGP430 CDM-T35W I FG GR SND 76P

CITY SOUL MINI, MASTERColour CDM-T, 35 W, Flat glass, Posttop for diameter 76 mm

CitySoul is a family of modular street-lighting luminaires featuring state-of-the-art lamp and gear technologies – including LED – and offering outstanding optical performance. Its classic design merges well with today's urban environment. The simple, flat, ellipsoidal form of the luminaire creates an elegant light-point. Suitable for side-entry, suspended or post-top installation, and with its adjustable beam and light trespass accessories, this versatile luminaire fits every application. CitySoul comes in two sizes, along with a complete range of dedicated masts and brackets.

Product data

General Information				
Lamp family code	CDM-T [MASTERColour CDM-T]			
Gear	CONV [Conventional]			
Photocell	-			
Product family code	CGP430 [CITY SOUL MINI]			
Embedded control	-			
CE mark	Yes			
ENEC mark	ENEC mark			
Light Technical				
Number of light sources	1			
Optical cover type	Flat glass			
Operating and Electrical				
Input Voltage	230 V			

Power Consumption	35 W				
Mechanical and Housing					
Housing Color	Grey				
Mounting device	Post-top for diameter 76 mm				
Overall length	644 mm				
Overall width	400 mm				
Approval and Application					
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]				
Mech. impact protection code	IK09 [10 J]				
Protection class IEC	Safety class I				
Product Data					
Full product code	871155947903300				
Order product name	CGP430 CDM-T35W I FG GR SND 76P				


Datasheet, 2023, September 4 data subject to change


CitySoul

Order code	910502207718		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	1		
Material Nr. (12NC)	910502207718		
Full product name	CGP430 CDM-T35W I FG GR SND 76P		


EAN/UPC - Case	8711559479033
EAN/UPC - Product/Case	8711559479033


Dimensional drawing














Product	Α	В	С	D
CGP430 CDM-T35W I FG GR SND 76P	171 mm	510 mm	644 mm	400 mm

