



Pentura Mini

TCH128 1xTL5-28W/830 HF

1, TL5, 28 W, 830 warm white, Electronic high-frequency

Pentura Mini TCH128 is an ultra-slim decorative batten for domestic applications. A cost-effective, ready-to-install mini fluorescent solution. Pentura Mini TCH128 offers the energy-saving benefits of miniature fluorescent lamp technology coupled with lightweight electronics and a patented internal reflector for improved lighting performance. The batten is easy to install e.g. over worktops and workstations in the home, home office and recreational environments, etc. it provides bright light where needed even where installation space is limited. Pentura Mini TCH128 battens are fitted with lamp, tough polycarbonate diffuser and all fixing accessories, reducing installation time to a minimum. The battens are through-wired with removeable end-caps at both ends covering the push-button connection blocks for simple connection and through-wiring.

Product data

General Information		
Lamp family code	TL5 [TL5]	
Gear	HF [Electronic high-frequency]	
CE mark	Yes	
Flammability mark	For mounting on normally flammable surfaces	
Glow-wire test	Temperature 850 °C, duration 5 s	
Light Technical		
Number of light sources	1	
Light source color	830 warm white	
Operating and Electrical		
Input Voltage	220 to 240 V	

Power Consumption	28 W
Mechanical and Housing	
Overall length	1,223 mm
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Protection class IEC	Safety class II
Application Conditions	
Suitable for random switching	Not applicable
Product Data	
Order product name	TCH128 1xTL5-28W/830 HF


Datasheet, 2023, April 29 data subject to change


Pentura Mini


Full product name	TCH128 1xTL5-28W/830 HF
Full product code	871155914856499
Order code	14856499
Material Nr. (12NC)	910502537818
Numerator - Quantity Per Pack	1

EAN/UPC - Product/Case	8711559148564
Numerator - Packs per outer box	16
EAN/UPC - Case	8711559804569

Dimensional drawing







Product	Α
TCH128 1xTL5-28W/830 HF	1,223 mm

